



Workbook. **2020-2021**

first edition july

GENERAL INFORMATION

Our production started off and continues to be of an artisanal nature. Our lamps are not produced in large series, from moulds or sophisticated plants but they are hand-crafted by our artisans. Slight flaws are thus not to be considered defects, but rather the typical characteristics of manual work.

Catellani & Smith declares under its own responsibility that its products meet the essential requirements of EC directives and comply with EN 60598 for luminaires and related components. Catellani & Smith lamps are built with a voltage of 220/240V.

The pricelist specifies which luminaires are compatible with a voltage of 110V (with standard EC components and not with UL certified components) and which ones can be compatible upon request, by making some styling and technical modifications (price estimate to be provided).

Production is tested 100%: each product undergoes a thorough quality control that guarantees it is intact and fully functional. The guarantee covers the item for 2 years from the date of purchase, including the right to a replacement or to the repair of the product or parts thereof affected by manufacturing defects detected at the time of purchase or that arise over the next two years. **The guarantee does not cover any damage to luminaires caused by connection to incompatible dimmers or control and dimming systems.** Compatibility of our products with dimmers or home automation systems must be checked prior to purchase and it is the responsibility of the customer or person acting for him/her.

The guarantee does not include any refunds for the intervention of qualified staff (electrician, etc.) or costs for the installation/disassembly or costs related to equipment (such as scaffolding access platforms, scaffolding, etc.) required to access the luminaires and perform maintenance and control operations on them.

It is advisable always to test the luminaires on the ground before final installation if they are to be fitted under special circumstances or connected to control and dimming systems.

In compliance with the regulations in force, **the manufacturer reserves the right to make any styling or technical changes without prior notice.**

Such changes also include the type and wattage of light bulbs and electronic parts. These changes are due to market availability issues since it is continuously growing and evolving, and it tends to eliminate certain products in favour of others, discontinuing their production without notice (which is increasingly often the case with LED bulbs).


The Catellani & Smith Workbook is designed to help and protect the customer in his/her choice of products. We therefore recommend that you read each section thoroughly, given the complexity of the electronic parts, and that you check the compatibility between the various components (such as dimmers, light sources, etc.) and contact qualified staff for the choice and installation of products.



Limited edition / Petits Bijoux / Petites Lentilles / Lederam / Sorry Giotto / Light Stick / Wa Wa / Atman / Giulietta / Jackie O / PostKrisi / Fil de Fer / Lucenera / Stchu-Moon / Macchina della Luce / Luci d'Oro / Turciù / Oggetti Senza Tempo / Medousê / More / Sypha / Fil de Fer Outdoor / Other Smiths

Limited edition

p. 6



Trenta

Petits Bijoux

p. 6



28 Petits Bijoux



56 Petits Bijoux

Petites Lentilles

p. 8




22 Petites Lentilles

Lederam

p. 10



Lederam Manta S1



Lederam Manta S2



Lederam Manta CWS1




Lederam C150/180



Lederam C1



Lederam C2



Lederam W



Lederam WF



Lederam WB1



Lederam W1



Lederam W2




Lederam T1




Lederam F0



Lederam F1




Lederam F2




Lederam F3

Sorry Giotto


p. 20




Sorry Giotto 9



Sorry Giotto 12



Sorry Giotto 1



Sorry Giotto 3




Light Stick


p. 22




Light Stick CW



Light Stick V



Light Stick T



Light Stick F

Wa Wa

p. 24



Wa Wa T



Wa Wa F



Wa Wa W



Miss Stick



Uau T



Uau F

Atman

p. 28




Atman

Giulietta

p. 30




Giulietta BE T




Giulietta BE F



Giulietta W



Giulietta T



Giulietta F

Jackie O


p. 32




Jackie O JC



Jackie O IC



Jackie O Chand. 6/9/12



Jackie O Chand. 15/20/24

PostKrisi

p. 34



PostKrisi 50-51-52



PostKrisi 10 Malagolina



PostKrisi F 100



PostKrisi F 60




PostKrisi T 40



PostKrisi W 21-40-60



PostKrisi CW 70



PostKrisi 49



PostKrisi T 61




PostKrisi F 64



PostKrisi 65-66-67



PostKrisi Chandelier



PK/SL Chandelier



PostKrisi W 71

Fil de Fer

p. 44



Fil de Fer



Fil de Fer Nuvola



Fil de Fer CW Ovale



Fil de Fer CW Ovale



Fil de Fer F



Sweet Light Chandelier



Sweet Light T



Uomo della Luce S

Lucenera

p. 48



Lucenera 200



Lucenera 500



Lucenera 504



Lucenera 502



Lucenera 503



Lucenera 506



Lucenera 206



Lucenera 202



Lucenera 207



Lucenera 208

Stchu-Moon


p. 54



Stchu-Moon 02 230V



Stchu-Moon 02



Stchu-Moon 02 Chand.



Stchu-Moon 05



Stchu-Moon 06



Stchu-Moon R



Stchu-Moon 08



Stchu-Moon 09



Stchu-Moon 01



Macchina della Luce

p. 60




mod. A




mod. B




mod. C



mod. D



mod. E



mod. F



mod. I




W mod. I



W mod. C

Luci d'Oro

p. 64



Malagola 27/55/110



Gold Moon IC/JC




Gold Moon Chandelier



DiscO



Telchisugìo



Luna W




Luna Piena



Full Moon




Francesca



Luce d'Oro T



Luce d'Oro F



Luna



Gemma



Colonna



Pepita

Turciù

p. 74



Turciù 36



Turciù 21



Turciù 16



Turciù 9



Turciù 9



Turciù 5



Turciù 3



Turciù 2



Bonsai



Sottovento



Albero della Luce



Oggetti Senza Tempo

p. 80



EC 301



Herem T



Ciclotalia T



Ciclotalia F



Lola T



Lola F



Ametista



Luce che dipinge



Miracolo



Nike



Shadow

Medousé (outdoor)

p. 86



Medousé W



Medousé F

More (outdoor)

p. 88



More



More O



More F

Sypha

p. 90



Syphasera



Syphasera



Syphaduepassi

Fil de Fer

p. 92



Fil de Fer



Fil de Fer F



Uomo della Luce XXL

Other Smiths

p. 94



Alchemie T



Technical information

p. 97

Mains voltage LED p. 98

Lederam: colour combinations and details p. 100

Chandelier p. 102

Macchina della Luce LED boards p. 104

Stchu-Moon LED boards p. 105

Outdoor: Gel box system p. 106

Outdoor: Quick connectors system p. 107

Outdoor accessories p. 108

Medousé installation suggestions p. 109

Installation suggestions for Sypha/More p. 110

PSU (Power Supply Unit) Kits p. 112


Dimming wiring diagrams p. 113



Limited edition

[*Finishes*] // **Brass** (an alloy of copper and zinc) is a very elegant finish, yellow-gold in colour, with an excellent corrosion resistance. It may oxidise, therefore regular cleaning helps preserving its original appearance and slow down the ageing process, which might be anyway accelerated by the weather, frequent handling or conditions of high humidity.

p. 13



Trenta / battery table lamp

TRENTA / glass bulb / brass-coated cover / burnished iron pedestal


battery	source	type	watt	lumen	K	CRI	en. class	battery charger	dimming
Li-ION 3,7V 1180 mAh	constant voltage	LED	1x1W	100	2700	80	A+	input 110/240V output 5V@1,2 A (EU plug only)	NO on/off switch included

Petits Bijoux

[*Finishes*] // **Satin brass** (an alloy of copper and zinc) is a very elegant finish, yellow-gold in colour, with an excellent corrosion resistance. We use it untreated, therefore it may oxidise with time. Regular cleaning helps preserving its original appearance and slow down the ageing process, which might be anyway accelerated by the weather, frequent handling or conditions of high humidity.

[*Note*] // (*) Our LEDs can be dimmed by using compatible dimmers tested specifically to dim very low loads. We suggest checking the minimum load of the dimmer before installation.

p. 17



28 Petits Bijoux / pendant lamp

PB28 / satin brass rings / white base / transparent covers with brass clips


voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V* or 240V	constant voltage 24V LED	interch. LED board	28x1W 28W	4004	2700	>80	A++	constant voltage driver	YES IGBT/Triac*

*110V version available with white base Ø 21x10,5 cm

weight 6 kg



p. 21



56 Petits Bijoux / pendant lamp

PB56 / satin brass rings / white base / transparent covers with brass clips

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	constant voltage 24V LED	interch. LED board	56x1W 56W	8008	2700	>80	A++	constant voltage driver	YES IGBT/Triac*


weight 13 kg

Petites Lentilles

[*Finishes*] // **Satin brass** (an alloy of copper and zinc) is a very elegant finish, yellow-gold in colour, with an excellent corrosion resistance. We use it untreated, therefore it may oxidise with time. Regular cleaning helps preserving its original appearance and slow down the ageing process, which might be anyway accelerated by the weather, frequent handling or conditions of high humidity.

[*Note*] // (*) The remote control provided allows to switch on and dim independently the LED strip on the base and the LEDs on the oval. The system (we use Casambi) can be programmed and controlled also via app.

p. 25



22 Petites Lentilles / pendant lamp

PL22 / satin brass oval / white base / transparent lens with brass holder

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
240V (110V av. on request)	constant voltage 24V LED	interch. LED board	22x1W 22W	3146	2700	>80	A++	constant voltage driver	wireless independent (remote control incl.)*
		low voltage LED strip (directed upwards)	4W	150					


weight 3,6 kg



Lederam

[Note] // (*) Mains voltage LED modules and COB LED are dimmable using IGBT (trailing edge) dimmers designed specifically for LED sources. Their dimming is extremely delicate: incompatible dimmers may cause irreparable damage to the LED. Some dimmers on the market have a NO button (Normally Open) or are specific connector socket-mounted or recessed. They are generally inserted into junction boxes; their limited thickness facilitates the installer's task and makes the dimmer fit for installation even in shallow boxes. Dimmers with an integrated radio dimmer for both manual (NO button) and wireless control are also available. It is important to note that during adjustment the dimming appears less precise, with some flickering. Furthermore some types of dimmer, even if they have been recommended by the manufacturers themselves, have visible flickering (almost essentially down to a minimum) depending on the mains and on the type of interference present. The problem can be solved by increasing the minimum value setting of the potentiometer on the dimmer. Low voltage DALI or 1...10V versions available on request.

p. 28




Lederam Manta S1 / pendant lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
LS13 / shade black/gold / black rod / gold disc / black base	110V or 240V	mains voltage LED	LED module	1x17W	1700	2700	> 80	A+	-	YES*
LS14 / shade black/copper / black rod / copper disc / black base										
LS15 / shade white/white / gold rod / white disc / white base										
LS16 / shade white/gold / satin rod / white disc / white base										
LS18 / shade white/white / satin rod / white disc / white base										
LS110 / shade white/white / white rod / white disc / white base										

weight 2 kg

p. 31




Lederam Manta S2 / pendant lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
LS23 / shade black/gold / black rods / gold discs / black bases	110V or 240V	mains voltage LED	LED module	2x17W 34W	3400	2700	> 80	A+	-	YES*
LS24 / shade black/copper / black rods / copper discs / black bases										
LS25 / shade white/white / gold rods / white discs / white bases										
LS26 / shade white/gold / satin rods / white discs / white bases										
LS28 / shade white/white / satin rods / white discs / white bases										

weight 5,5 kg

p. 32




Lederam Manta CWS1 / ceiling or wall lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
LCWS13 / shade black/gold / black rod / gold disc / black base	110V or 240V	mains voltage LED	LED module	1x17W	1700	2700	> 80	A+	-	YES*
LCWS14 / shade black/copper / black rod / copper disc / black base										
LCWS15 / shade white/white / gold rod / white disc / white base										
LCWS16 / shade white/gold / satin rod / white disc / white base										
LCWS18 / shade white/white / satin rod / white disc / white base										
LCWS110 / shade white/white / white rod / white disc / white base										




p. 33

**Lederam C150 / ceiling lamp**

- LC1503 / shade black/gold / black rod / gold disc / black base
- LC1504 / shade black/copper / black rod / copper disc / black base
- LC1505 / shade white/white / gold rod / white disc / white base
- LC1506 / shade white/gold / satin rod / white disc / white base
- LC1508 / shade white/white / satin rod / white disc / white base
- LC15010 / shade white/white / white rod / white disc / white base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	mains voltage LED	LED module	1x17W	1700	2700	> 80	A+	-	YES*


p. 33

**Lederam C180 / ceiling lamp**

- LC1803 / shade black/gold / black rod / gold disc / black base
- LC1804 / shade black/copper / black rod / copper disc / black base
- LC1805 / shade white/white / gold rod / white disc / white base
- LC1806 / shade white/gold / satin rod / white disc / white base
- LC1808 / shade white/white / satin rod / white disc / white base
- LC18010 / shade white/white / white rod / white disc / white base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	mains voltage LED	COB LED	1x30W	2190	2700	90	A+	-	YES*


p. 36

**Lederam C1 / ceiling lamp**

- LC12 / black disc / satin rod / black base
- LC13 / gold disc / black rod / black base
- LC14 / copper disc / black rod / black base
- LC15 / white disc / gold rod / white base
- LC16 / white disc / satin rod / white base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	mains voltage LED	LED module	1x17W	1700	2700	> 80	A+	-	YES*

p. 37


**Lederam C2 / ceiling lamp**

- LC22 / black discs / satin rods / black base
- LC23 / gold discs / black rods / black base
- LC24 / copper discs / black rods / black base
- LC25 / white discs / gold rods / white base
- LC26 / white discs / satin rods / white base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	mains voltage LED	LED module	2x17W 34W	3400	2700	> 80	A+	-	YES*




p. 39

**Lederam W 17 / wall lamp**

- LW171 / disc D1 black/copper - disc D2 copper/black / black base
- LW172 / disc D1 black/gold - disc D2 gold/black / black base
- LW173 / disc D1 gold/gold - disc D2 gold/white / white base
- LW174 / disc D1 copper/copper - disc D2 copper/white / white base
- LW175 / disc D1 white/gold - disc D2 gold/white / white base
- LW176 / disc D1 white/copper - disc D2 copper/white / white base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	mains voltage LED	LED module	1x17W	1700	2700	> 80	A+	-	YES*


p. 39

**Lederam W 25 / wall lamp**

- LW251 / discs D1 black/copper - disc D2 copper/black / black base
- LW252 / discs D1 black/gold - disc D2 gold/black / black base
- LW253 / discs D1 gold/gold - disc D2 gold/white / white base
- LW254 / discs D1 copper/copper - disc D2 copper/white / white base
- LW255 / discs D1 white/gold - disc D2 gold/white / white base
- LW256 / discs D1 white/copper - disc D2 copper/white / white base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	mains voltage LED	LED module	1x17W	1700	2700	> 80	A+	-	YES*


p. 40

**Lederam WF 17 / wall lamp**

- LWF171 / black disc / black base
- LWF173 / gold/white disc / white base
- LWF174 / copper/white disc / white base
- LWF176 / white disc / white base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	mains voltage LED	LED module	1x17W	1700	2700	> 80	A+	-	YES*

p. 40


**Lederam WF 25 / wall lamp**

- LWF251 / black disc / black base
- LWF253 / gold/white disc / white base
- LWF254 / copper/white disc / white base
- LWF256 / white disc / white base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	mains voltage LED	LED module	1x28W	2580	2700	80	A+	-	YES*



p. 41


**Lederam WB1 / wall lamp**

- LWB12 / black disc / satin rod / black base
- LWB13 / gold disc / black rod / black base
- LWB14 / copper disc / black rod / black base
- LWB15 / white disc / gold rod / white base
- LWB16 / white disc / satin rod / white base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	mains voltage LED	LED module	1x17W	1700	2700	> 80	A+	-	YES*

Available on request with disc on the right.


p. 43

**Lederam W1 17 / wall lamp**

- LW1171 / black disc / black base
- LW1173 / gold/black disc / black base
- LW1174 / copper/black disc / black base
- LW1176 / white disc / white base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	mains voltage LED	LED module	1x17W	1700	2700	> 80	A+	-	YES*


p. 43

**Lederam W1 25 / wall lamp**

- LW1251 / disc Ø 25 cm black / black base
- LW1253 / disc Ø 25 cm gold/black / black base
- LW1254 / disc Ø 25 cm copper/black/ black base
- LW1256 / disc Ø 25 cm white / white base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	mains voltage LED	LED module	1x17W	1700	2700	> 80	A+	-	YES*

p. 45


**Lederam W2 / wall lamp**

- LW22 / black discs / satin rods / black base
- LW23 / gold discs / black rods / black base
- LW24 / copper discs / black rods / black base
- LW25 / white discs / gold rods / white base
- LW26 / white discs / satin rods / white base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	mains voltage LED	LED module	2x17W 34W	3400	2700	> 80	A+	-	YES*



p. 47


**Lederam T1 / table lamp**

- LT12 / black disc / satin rod / black base/cable/dimmer
- LT13 / gold disc / black rod / black base/cable/dimmer
- LT14 / copper disc / black rod / black base/cable/dimmer
- LT15 / white disc / gold rod / white base/cable/dimmer
- LT16 / white disc / satin rod / white base/cable/dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
240V (110V available with on/off)	mains voltage LED	LED module	1x17W	1400	2700	80	A+	-	included (memory 0%)




p. 48

**Lederam F0 / standing lamp**

- LF012 / brass disc / black rod / black base/cable/dimmer
- LF02 / black disc / satin rod / black base/cable/dimmer
- LF03 / gold disc / black rod / black base/cable/dimmer
- LF04 / copper disc / black rod / black base/cable/dimmer
- LF06 / white disc / satin rod / white base/cable/dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110V or 240V	mains voltage LED	COB LED	1x30W	2190	2700	90	A+	-	included (memory last step)


p. 49

**Lederam F1 / standing lamp**

- LF12 / black disc / satin rod / black base/cable/dimmer
- LF13 / gold disc / black rod / black base/cable/dimmer
- LF14 / copper disc / black rod / black base/cable/dimmer
- LF15 / white disc / gold rod / white base/cable/dimmer
- LF16 / white disc / satin rod / white base/cable/dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110V or 240V	mains voltage LED	LED module	1x17W	1400	2700	80	A+	-	included (memory last step)

p. 50


**Lederam F2 / standing lamp**

- LF22 / black discs / satin rods / black base/cable/dimmer
- LF23 / gold discs / black rods / black base/cable/dimmer
- LF24 / copper discs / black rods / black base/cable/dimmer
- LF25 / white discs / gold rods / white base/cable/dimmer
- LF26 / white discs / satin rods / white base/cable/dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
240V (110V available with on/off)	mains voltage LED	LED module	2x17W 34W	3400	2700	> 80	A+	-	included (memory last step)



p. 52

**Lederam F3** / standing lamp

- LF32 / black discs / satin rod / black base/cable/dimmer
- LF33 / gold discs / black rod / black base/cable/dimmer
- LF34 / copper discs / black rod / black base/cable/dimmer
- LF35 / white discs / gold rod / white base/cable/dimmer
- LF36 / white discs / satin rod / white base/cable/dimmer


voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
240V (110V available with on/off)	mains voltage LED	LED module	3x17W 51W	5100	2700	> 80	A+	-	included (memory last step)

Sorry Giotto

[*Finishes*] // **Hand painting** is chosen for its deliberate textured effect and uniqueness of result. Any irregularities or unevenness in the coating cannot be considered defect, but rather a hallmark of the artisanal crafting process. / **Rough iron** (untreated metal) is chosen by the designer specifically because of its uniqueness and its natural ageing property. The appearance of any uneven rust patches does not constitute a defect, since it is a typical sign of the ageing process, which might be considerably accelerated in conditions of high humidity or direct exposure to outdoor weathering.

[*Note*] // (*) The plug driver 110-240V is supplied with the electrical plug suitable for the market of reference only. Please specify in stage of order if the destination of the product differs from your standard.


p. 58

**Sorry Giotto 9 / 12** / pendant lamp with floor connection

- SG9 / ring Ø 90 cm blue / black anvil / blue wires / black dimmer
- SG12 / ring Ø 120 cm blue / black anvil / blue wires / black dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110-240V	constant current LED 350 mA	interch. LED	12x1W 12W	1200	2700	80	A+	constant current plug driver*	included (memory last step)
			15x1W 15W	1500					

p. 59


**Sorry Giotto 1** / table lamp

- SG1 / blue ring / rough iron base / blue wire / nickel/black dimmer
- SG1PL / blue ring / rough iron base / blue wire / nickel/black dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
220-240V (EU plug only)	constant current LED 350 mA	interch. LED	4x1W 4W	400	2700	80	A+	constant current plug driver (EU plug only)	included (memory 100%)
110-240V (all other plugs)	constant current LED 350 mA	interch. LED	4x1W 4W	400	2700	80	A+	constant current plug driver (all other plugs)*	included (memory last step)



p. 60

**Sorry Giotto 3 / standing lamp**

SG3 / blue rings / black base and stem / blue wires / black dimmer


voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110-240V	constant current LED 350 mA	interch. LED	16x1W 16W	1600	2700	80	A+	constant current plug driver*	included (memory last step)

Light Stick

[Finishes] // **Nickel coating** (metal plating process) is chosen by the designer for its elegant and warm finish. To prevent any natural oxidation process, it requires regular cleaning. In alternative to nickel coating, customized finishes (i.e. chrome plating) can be provided upon request.

[Note] // (*) Our LEDs can be dimmed by using compatible dimmers tested specifically to dim very low loads. We suggest checking the minimum load of the dimmer before installation. / (**) The plug driver 110-240V is supplied with the electrical plug suitable for the market of reference only. Please specify in stage of order if the destination of the product differs from your standard.

p. 65

**Light Stick CW / wall or ceiling lamp**

LSP4 / nickel rod and base

LSP4G / satin gold rod and base

LSP6 / nickel rod and base

LSP6G / satin gold rod and base


LSP8 / nickel rod and base

LSP8G / satin gold rod and base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
240V (110V available with not dimmable driver)	constant current LED 350 mA	interch. LED	4x1W 4W	400	2700	80	A+	constant current driver	YES IGBT/Triac*
			6x1W 6W	600					
240V (110V available on request)	constant current LED 350 mA	interch. LED	8x1W 8W	800	2700	80	A+	constant current driver	YES IGBT/Triac*

base Ø 9x3 cm / H ledge 17 cm

p. 66

**Light Stick V / wall lamp**

LSPV6 / nickel vertical rod and base


LSPV6G / satin gold vertical rod and base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
240V (110V available with not dimmable driver)	constant current LED 350 mA	interch. LED	6x1W 6W	600	2700	80	A+	constant current driver	YES IGBT/Triac*

H ledge 17 cm



p. 67




Light Stick T / table lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
LS6 / nickel rod / burnished base / black cable / nickel/black dimmer	110-240V	constant current LED 350 mA	interch. LED	6x1W 6W	600	2700	80	A+	constant current plug driver**	included (memory last step)
LS6G / satin gold rod / black base / black cable / black dimmer										



p. 69



Light Stick F / standing lamp


	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
LSF10B / black rod / black base / black wires / black dimmer	110-240V	constant current LED 350 mA	interch. LED	10x1W 10W	1000	2700	80	A+	constant current plug driver**	included (memory last step)
LSF10 / nickel rod / black base / black wires / black dimmer										
LSF10G / satin gold rod / black base / black wires / black dimmer										

Wa Wa

[*Finishes*] // **Nickel coating** (metal plating process) is chosen by the designer for its elegant and warm finish. To prevent any natural oxidation process, it requires regular cleaning. In alternative to nickel coating, customized finishes (i.e. chrome plating) can be provided upon request. / **Brass** (an alloy of copper and zinc) is a very elegant finish, yellow-gold in colour, with an excellent corrosion resistance. We use it untreated, therefore it may oxidise with time. Regular cleaning helps preserving its original appearance and slow down the ageing process, which might be anyway accelerated by the weather, frequent handling or conditions of high humidity. / **Copper** is a very malleable and ductile metal, chosen for its high thermal and electrical conductivity, as well as for its typical reddish-orange colour. We use it untreated, therefore it may oxidise with time, forming a green patina. Regular cleaning helps preserving its original appearance and slow down the ageing process, which might be anyway accelerated by the weather, frequent handling or conditions of high humidity.

[*Note*] // (*****) Our LEDs can be dimmed by using compatible dimmers tested specifically to dim very low loads. We suggest checking the minimum load of the dimmer before installation. / (******) The plug driver 110-240V is supplied with the electrical plug suitable for the market of reference only. Please specify in stage of order if the destination of the product differs from your standard.

p. 72




Wa Wa T / table lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
WW / nickel structure, base and sticks / glass lens / blue wires / nickel/black dimmer	110-240V	constant current LED 350 mA	interch. LED	3x1W 3W	300	2700	80	A+	constant current plug driver**	included (memory last step)



p. 74




Wa Wa F / standing lamp

WWF / nickel structure, base and sticks / glass lens / black wires / black dimmer
 WWFBR / brass base and structure / copper sticks / glass lens / black wires / black dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110-240V	constant current LED 350 mA	interch. LED	5x1W 5W	500	2700	80	A+	constant current plug driver**	included (memory last step)

base cod. WWF: 20x20 cm
 base cod. WWFBR: 16x16 cm

p. 76




Wa Wa W / wall lamp

WWP / nickel structure, base and sticks / glass lens / blue wires

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
240V (110V available not dimmable)	constant current LED 350 mA	interch. LED	3x1W 3W	300	2700	80	A+	constant current driver	YES IGBT/Triac*

H ledge 26 cm

p. 77




Miss Stick / table lamp

MS / nickel structure and base / glass lens / blue wire / nickel/black dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110-240V	constant current LED 350 mA	interch. LED	1x1W	100	2700	80	A+	constant current plug driver**	included (memory last step)

p. 78




Uau T / table lamp

UAU / nickel structure and base / glass lens / blue wire / nickel/black dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110-240V	constant current LED 350 mA	interch. LED	1x1W	100	2700	80	A+	constant current plug driver**	included (memory last step)



p. 79



Uau F / standing lamp


UAUF / nickel structure and base / glass lens / blue wire / nickel/black dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110-240V	constant current LED 350 mA	interch. LED	1x1W	100	2700	80	A+	constant current plug driver**	included (memory last step)

Atman

[Note] // (*) The plug driver 110-240V is supplied with the electrical plug suitable for the market of reference only. Please specify in stage of order if the destination of the product differs from your standard.

p. 82



Atman / table lamp

AT / oval crystal glass / nickel base / blue wire / nickel/black dimmer


ATPL / oval crystal glass / nickel base / blue wire / nickel/black dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
220-240V (EU plug only)	constant current LED 350 mA	interch. LED	1x1W	100	2700	80	A+	constant current plug driver (EU plug only)	included (memory 100%)
110-240V (all other plugs)	constant current LED 350 mA	interch. LED	1x1W	100	2700	80	A+	constant current plug driver (all other plugs)*	included (memory last step)



Giulietta

p. 87




Giulietta BE T / battery table lamp

GBB / black hoop and base / brass rod
 GBBR / vintage brass hoop and base / brass rod

battery	source	type	watt	lumen	K	CRI	en. class	battery charger	dimmer
Li-ION 3,7V 4100 mAh	constant voltage	LED board	1x2,8W	283	2700	>90	A+	input 110/240V output 5V@1,2 A (EU plug only)	included touch

p. 88




Giulietta BE F / battery standing lamp

GBFB / black hoop and base / brass rod
 GBFBR / vintage brass hoop and base / brass rod

battery	source	type	watt	lumen	K	CRI	en. class	battery charger	dimmer
Li-ION 3,7V 4100 mAh	constant voltage	LED board	1x2,8W	283	2700	>90	A+	input 110/240V output 5V@1,2 A (EU plug only)	included touch

p. 90




Giulietta W / wall lamp

GPB / black structure / black hoop
 GPNC / black structure / nickel hoop

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	constant voltage LED 5V	LED board	1x2,8W	283	2700	>90	A+	constant voltage driver	included touch-less (memory last step)




p. 91

**Giuletta T / USB table lamp**

GB / black structure / black hoop / black wire
 GNC / black structure / nickel hoop / black wire

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110-240V	constant voltage LED 5V	LED board	1x2,8W	283	2700	>90	A+	USB plug driver 5V (EU plug only)	included touch-less (memory last step)

p. 93

**Giuletta F / USB standing lamp**

GFB / nickel base and rod / black flex / black hoop / black wire
 GFNC / nickel base and rod / black flex / nickel hoop / black wire


voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110-240V	constant voltage LED 5V	LED board	1x2,8W	283	2700	>90	A+	USB plug driver 5V (EU plug only)	included touch-less (memory last step)

Jackie O

[*Finishes*] // **Nickel coating** (metal plating process) is chosen by the designer for its elegant and warm finish. To prevent any natural oxidation process, it requires regular cleaning. In alternative to nickel coating, customized finishes (i.e. chrome plating) can be provided upon request. / **Satin steel** - the standard modular metal bases are composed of a satin steel plate mounted on a white lacquered metal frame and fixed to it by nickel square-head screws. On request we can supply the plate white matt lacquered as the frame.

[*Note*] // (*) Our LEDs can be dimmed by using compatible dimmers tested specifically to dim very low loads. We suggest checking the minimum load of the dimmer before installation.

p. 97

**Jackie O JC / IC / pendant lamp**


JOJC / mod. JC / nickel jack connection / blue wire / nickel curl
 JOIC / mod. IC / nickel plate with tensioner / blue wire / nickel curl

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
-	constant current LED 350 mA	LED Jack/interch.	1x1W	100	2700	80	A+	not included available on request	-
		interch. LED							

installation hole Jackie O JC Ø 1,25 cm
 installation hole Jackie O IC Ø 5,5 cm




p. 98

**Jackie O Chandelier 6 / 9 / 12 / pendant lamp**

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
JO6Q / satin steel base 30x30 cm / blue wires / nickel curls	230V (110V available 1...10V/Push dimm.)	constant current LED 350 mA	LED Jack/interch.	6x1W 6W	600	2700	80	A+	constant current driver	YES IGBT/Triac*
JO9Q / satin steel base 30x30 cm / blue wires / nickel curls				9x1W 9W	900					
JO12Q / satin steel base 30x30 cm / blue wires / nickel curls				12x1W 12W	1200					

p. 98

**Jackie O Chandelier 15 / 20 / 24 / pendant lamp**


	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming		
JO15Q / satin steel base 60x60 cm / blue wires / nickel curls	110V or 240V	constant current LED 350 mA	LED Jack/interch.	15x1W 15W	1500	2700	80	A+	constant current driver	YES IGBT/Triac*		
JO15R / satin steel base 150x30 cm / blue wires / nickel curls				20x1W 20W	2000							
JO20Q / satin steel base 60x60 cm / blue wires / nickel curls											24x1W 24W	2400
JO20R / satin steel base 150x30 cm / blue wires / nickel curls												
JO24Q / satin steel base 60x60 cm / blue wires / nickel curls												
JO24R / satin steel base 150x30 cm / blue wires / nickel curls												

PostKrisi

[*Finishes*] // **Hand painting** is chosen for its deliberate textured effect and uniqueness of result. Any irregularities or unevenness in the coating cannot be considered defect, but rather a hallmark of the artisanal crafting process. / **Brass** (an alloy of copper and zinc) is a very elegant finish, yellow-gold in colour, with an excellent corrosion resistance. We use it untreated, therefore it may oxidise with time. Regular cleaning helps preserving its original appearance and slow down the ageing process, which might be anyway accelerated by the weather, frequent handling or conditions of high humidity. / **Copper** is a very malleable and ductile metal, chosen for its high thermal and electrical conductivity, as well as for its typical reddish-orange colour. We use it untreated, therefore it may oxidise with time, forming a green patina. Regular cleaning helps preserving its original appearance and slow down the ageing process, which might be anyway accelerated by the weather, frequent handling or conditions of high humidity. / **Nickel coating** (metal plating process) is chosen by the designer for its elegant and warm finish. To prevent any natural oxidation process, it requires regular cleaning. In alternative to nickel coating, customized finishes (i.e. chrome plating) can be provided upon request. / **Satin steel** - the standard modular metal bases are composed of a satin steel plate mounted on a white lacquered metal frame and fixed to it by nickel square-head screws. On request we can supply the plate white matt lacquered as the frame.

[*Note*] // (*) LED bulbs can be dimmed using compatible dimmers, which have been tested specifically for dimming very low loads. The manufacturers of LED bulbs are required to draw up a list of suggested dimmers for the dimming of their products, with an indication of the maximum number of bulbs dimmable with the various types of dimmer. / (**) Mains voltage LED modules and COB LED are dimmable using IGBT (trailing edge) dimmers designed specifically for LED sources. Their dimming is extremely delicate: incompatible dimmers may cause irreparable damage to the LED. Some dimmers on the market have a NO button (Normally Open) or are specific connector socket-mounted or recessed. They are generally inserted into junction boxes; their limited thickness facilitates the installer's task and makes the dimmer fit for installation even in shallow boxes. Dimmers with an integrated radio dimmer for both manual (NO button) and wireless control are also available. It is important to note that during adjustment the dimming appears less precise, with some flickering. Furthermore some types of dimmer, even if they have been recommended by the manufacturers themselves, have visible flickering (almost essentially down to a minimum) depending on the mains and on the type of interference present. The problem can be solved by increasing the minimum value setting of the potentiometer on the dimmer. Low voltage DALI or 1...10V versions available on request. / (***) The plug driver 110-240V is supplied with the electrical plug suitable for the market of reference only. Please specify in stage of order if the destination of the product differs from your standard.

p. 102

**PostKrisi 50 / 51 / pendant lamp**


	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
PK50LN / PostKrisi 50 / shade 85x35 cm natural / metal braided cable / nickel base	110V (bulb not supplied)-240V	mains voltage LED	E27 bulb	1x8W	1055	2700	≥80	A++	-	YES IGBT/Triac*
PK50LW / PostKrisi 50 / shade 85x35 cm white / metal braided cable / nickel base										
PK50LG / PostKrisi 50 / shade 85x35 cm gold / metal braided cable / nickel base										
PK50LS / PostKrisi 50 / shade 85x35 cm silver / metal braided cable / nickel base										
PK51LN / PostKrisi 51 / shade 115x40 cm natural / metal braided cable / nickel base										
PK51LW / PostKrisi 51 / shade 115x40 cm white / metal braided cable / nickel base										
PK51LG / PostKrisi 51 / shade 115x40 cm gold / metal braided cable / nickel base										
PK51LS / PostKrisi 51 / shade 115x40 cm silver / metal braided cable / nickel base										

weight: PK50 1,5 kg / PK51 2,8 kg

Available on request with LED silver crowned bulb (code LLC31)



p. 102



PostKrisi 52 / pendant lamp

- PK52LN / natural shade / grey braided cables / nickel base
- PK52LW / white shade / grey braided cables / nickel base
- PK52LG / gold shade / grey braided cables / nickel base
- PK52LS / silver shade / grey braided cables / nickel base


Available on request with LED silver crowned bulbs (code LLC31)



	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
PK52LN / natural shade / grey braided cables / nickel base	110V (bulbs not supplied)-240V	mains voltage LED	E27 bulb	3x8W 24W	3165	2700	≥80	A++	-	YES IGBT/Triac*
PK52LW / white shade / grey braided cables / nickel base										
PK52LG / gold shade / grey braided cables / nickel base										
PK52LS / silver shade / grey braided cables / nickel base										

weight 3 kg

p. 105




PostKrisi 10 Malagolina / table lamp

- PKM10LN / natural shade / nickel base and structure / blue wire / nickel/black dimmer
- PKM10LW / white shade / nickel base and structure / blue wire / nickel/black dimmer
- PKM10LG / gold shade / nickel base and structure / blue wire / nickel/black dimmer
- PKM10LS / silver shade / nickel base and structure / blue wire / nickel/black dimmer

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
PKM10LN / natural shade / nickel base and structure / blue wire / nickel/black dimmer	110-240V	constant current LED 350 mA	interch. LED	2x1W 2W	200	2700	80	A+	constant current plug driver***	included (memory last step)
PKM10LW / white shade / nickel base and structure / blue wire / nickel/black dimmer										
PKM10LG / gold shade / nickel base and structure / blue wire / nickel/black dimmer										
PKM10LS / silver shade / nickel base and structure / blue wire / nickel/black dimmer										

p. 106




PostKrisi F 100 / standing lamp

- PKF100W / white shade / nickel base and structure / black wires / black dimmer
- PKF100G / gold shade / nickel base and structure / black wires / black dimmer
- PKF100S / silver shade / nickel base and structure / black wires / black dimmer

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
PKF100W / white shade / nickel base and structure / black wires / black dimmer	110-240V	constant current LED 350 mA	interch. LED	8x1W 8W	800	2700	80	A+	constant current plug driver***	included (memory last step)
PKF100G / gold shade / nickel base and structure / black wires / black dimmer										
PKF100S / silver shade / nickel base and structure / black wires / black dimmer										

p. 107




PostKrisi F 60 / standing lamp

- PKF60LW / white shade / nickel base and structure / black wires / black dimmer
- PKF60LG / gold shade / nickel base and structure / black wires / black dimmer
- PKF60LS / silver shade / nickel base and structure / black wires / black dimmer

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
PKF60LW / white shade / nickel base and structure / black wires / black dimmer	110-240V	constant current LED 350 mA	interch. LED	3x1W 3W	300	2700	80	A+	constant current plug driver***	included (memory last step)
PKF60LG / gold shade / nickel base and structure / black wires / black dimmer										
PKF60LS / silver shade / nickel base and structure / black wires / black dimmer										




p. 108

**PostKrisi T 40 / table lamp**

PK40LW / white shade / nickel base and structure / blue wire / nickel/black dimmer
 PK40LG / gold shade / nickel base and structure / blue wire / nickel/black dimmer
 PK40LS / silver shade / nickel base and structure / blue wire / nickel/black dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110-240V	constant current LED 350 mA	interch. LED	2x1W 2W	200	2700	80	A+	constant current plug driver***	included (memory last step)

p. 109


**PostKrisi W 21 / 40 / 60 / wall lamp**

PKP21LN / PostKrisi W 21 / shade Ø 21 cm natural / nickel base
 PKP21LW / PostKrisi W 21 / shade Ø 21 cm white / nickel base
 PKP21LG / PostKrisi W 21 / shade Ø 21 cm gold / nickel base
 PKP21LS / PostKrisi W 21 / shade Ø 21 cm silver / nickel base
 PKP40LW / PostKrisi W 40 / shade Ø 40 cm white / nickel base
 PKP40LG / PostKrisi W 40 / shade Ø 40 cm gold / nickel base
 PKP40LS / PostKrisi W 40 / shade Ø 40 cm silver / nickel base
 PKP60LW / PostKrisi W 60 / shade Ø 60 cm white / nickel base
 PKP60LG / PostKrisi W 60 / shade Ø 60 cm gold / nickel base
 PKP60LS / PostKrisi W 60 / shade Ø 60 cm silver / nickel base

Ø 21 cm: rod H 22 cm
 Ø 40 cm: rod H 60 cm
 Ø 60 cm: rod H 80 cm

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
240V (110V available with not dimmable driver)	constant current LED 350 mA	interch. LED	2x1W 2W	200	2700	80	A+	constant current driver	NO av. on request


p. 111

**PostKrisi CW 70 / ceiling or wall lamp**

PKCW7LG / gold shade
 PKCW7LS / silver shade

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	mains voltage LED	COB LED	1x30W	2190	2700	90	A+	-	YES**

p. 113

**PostKrisi 49 / pendant lamp**

PK494LWG / shade Ø 40 cm white/gold / white braided cable / white base
 PK494LWS / shade Ø 40 cm white/silver / white braided cable / white base
 PK496LWG / shade Ø 60 cm white/gold / white braided cable / white base
 PK496LWS / shade Ø 60 cm white/silver / white braided cable / white base


voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulb not supplied)-240V	mains voltage LED	E27 bulb	1x8W	1055	2700	≥80	A++	-	YES IGBT/Triac*

Available on request with LED silver crowned bulb (code LLC31)

weight: Ø 40 cm 1 kg / Ø 60 cm 1,5 kg



p. 103



PostKrisi 49 / pendant lamp

- PK498LWG / shade Ø 80 cm white/gold / white braided cable / white base
- PK498LWS / shade Ø 80 cm white/silver / white braided cable / white base
- PK4910LWG / shade Ø 100 cm white/gold / white braided cable / white base
- PK4910LWS / shade Ø 100 cm white/silver / white braided cable / white base


Available on request with LED silver crowned bulbs (code LLC31)



voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulbs not supplied)-240V	mains voltage LED	E27 bulb	3x8W 24W	3165	2700	≥80	A++	-	YES IGBT/Triac*

weight: Ø 80 cm 2,8 kg / Ø 100 cm 3 kg

p. 115




PostKrisi T 61 / table lamp

- PK61LN / natural shades / black base / brass rod / black cable and dimmer
- PK61LNNC / natural shades / nickel rod and base / black cable and dimmer
- PK61LW / white shades / black base / brass rod / black cable and dimmer
- PK61LWNC / white shades / nickel rod and base / black cable and dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110V (bulbs not supplied)-240V	mains voltage LED	E27 bulb	3x8W 24W	2700	2700	≥80	A++	-	included (memory last step)

p. 116




PostKrisi F 64 / standing lamp

- PK64LN / natural shades / black base / brass rod / black cable and dimmer
- PK64LNNC / natural shades / nickel rod and base / black cable and dimmer
- PK64LW / white shades / black base / brass rod / black cable and dimmer
- PK64LWNC / white shades / nickel rod and base / black cable and dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110V (bulbs not supplied)-240V	mains voltage LED	E27 bulb	3x8W 24W	2700	2700	≥80	A++	-	included (memory last step)

p. 118



PostKrisi 65 / pendant lamp


- PK65LN / shades Ø 40 cm natural / brass structure / black cable and base
- PK65LNNC / shades Ø 40 cm natural / nickel structure and base / black cable
- PK65LW / shades Ø 40 cm white / brass structure / black cable and base
- PK65LWNC / shades Ø 40 cm white / nickel structure and base / black cable

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulbs not supplied)-240V	mains voltage LED	E27 bulb	3x8W 24W	3165	2700	≥80	A++	-	YES IGBT/Triac*

H 200 cm / H rod 63 cm / weight 2,5 kg



p. 118


**PostKrisi 66 / pendant lamp**

- PK66LN / shades Ø 60 cm natural / brass structure / black cable and base
- PK66LNNC / shades Ø 60 cm natural / nickel structure and base / black cable
- PK66LW / shades Ø 60 cm white / brass structure / black cable and base
- PK66LWNC / shades Ø 60 cm white / nickel structure and base / black cable

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulbs not supplied)-240V	mains voltage LED	E27 bulb	3x8W 24W	3165	2700	≥80	A++	-	YES IGBT/Triac*

H 210 cm / H rod 83 cm / weight 3,5 kg

p. 118


**PostKrisi 67 / pendant lamp**

- PK67LN / shades Ø 80 cm natural / brass structure / black cable and base
- PK67LNNC / shades Ø 80 cm natural / nickel structure and base / black cable
- PK67LW / shades Ø 80 cm white / brass structure / black cable and base
- PK67LWNC / shades Ø 80 cm white / nickel structure and base / black cable

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulbs not supplied)-240V	mains voltage LED	E27 bulb	3x8W 24W	3165	2700	≥80	A++	-	YES IGBT/Triac*

H 220 cm / H rod 100 cm / weight 5 kg

p. 120

**PostKrisi Chandelier / pendant lamp**

- CPK3QL / satin base 30x30 cm / 3x PK14 / H 180 cm
- CPK5QL / satin base 30x30 cm / 5x PK14 / H 180 cm
- CPK7CL / satin base Ø 40 cm / 7x PK14 / H 180 cm
- CPK7QL / satin base 60x60 cm / 7x PK14 / H 180 cm
- CPK7RL / satin base 90x30 cm / 3x PK20 and 4x PK14 / H 180 cm
- CPK10CL / satin base Ø 78 cm / 4x PK20 and 6x PK14 / H 300 cm

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	extra-low-voltage 12V DC LED	G4 bulb	3x1,5W 4,5W	450	2700	85	A+	low voltage driver	YES Triac*
			5x1,5W 7,5W	750					
			7x1,5W 10,5W	1050					
			10x1,5W 15W	1500					

*PK14 = PostKrisi sphere Ø 14 cm natural with jack**PK20 = PostKrisi sphere Ø 20 cm natural with jack*

p. 120

**PostKrisi/Sweet Light Chandelier / pendant lamp**


- CPKSL7CL / satin base Ø 40 cm / 3x PK14 and 4x SL / H 180 cm
- CPKSL15CL / satin base Ø 78 cm / 6x PK14 and 9x SL / H 300 cm
- CPKSL24RL / satin base 150x30 cm / 9x PK14 and 15x SL / H 400 cm
- CPKSL35QL / satin base 90x90 cm / 15x PK14 and 20x SL / H 400 cm
- CPKSL50RL / satin base 150x60 cm / 16x PK14 and 34x SL / H 400 cm

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	extra-low-voltage 12V DC LED	G4 bulb	7x1,5W 10,5W	1050	2700	85	A+	low voltage driver	YES Triac*
			15x1,5W 22,5W	2250					
			24x1,5W 36W	3600					
			35x1,5W 52,5W	5250					
			50x1,5W 75W	7500					

*PK14 = PostKrisi sphere Ø 14 cm natural with jack**SL = Sweet Light Ø 10 cm aluminium with jack**For further models see also Sweet Light Chandelier page 46*



p. 121



PostKrisi W 71 / wall or ceiling lamp

PK71STLBU / blue
 PK71STLR / red
 PK71STLW / white
 PK71STLY / yellow

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
240V (110V available on request)	constant voltage 24V LED	low voltage LED strip	60W	8000	3000	>95	A++	constant voltage driver	YES DALI / 1 ... 10V / PUSH


H ledge 15 cm

Fil de Fer

[*Finishes*] // **Nickel coating** (metal plating process) is chosen by the designer for its elegant and warm finish. To prevent any natural oxidation process, it requires regular cleaning. In alternative to nickel coating, customized finishes (i.e. chrome plating) can be provided upon request. / **Rough iron** (untreated metal) is chosen by the designer specifically because of its uniqueness and its natural ageing property. The appearance of any uneven rust patches does not constitute a defect, since it is a typical sign of the ageing process, which might be considerably accelerated in conditions of high humidity or direct exposure to outdoor weathering.

[*Cables*] // **(s)** suspension cable. / **(el)** electrical cable.

p. 124



Fil de Fer / pendant lamp

F5SL / Ø 50 cm aluminium / steel cable^(s) / grey braided cable^(el) / nickel base
 F5SLG / Ø 50 cm matt gold anodized / steel cable^(s) / gold braided cable^(el) / gold-plated base
 F7SL / Ø 70 cm aluminium / steel cable^(s) / grey braided cable^(el) / nickel base
 F7SLG / Ø 70 cm matt gold anodized / steel cable^(s) / gold braided cable^(el) / gold-plated base
 F10SL / Ø 100 cm aluminium / steel cable^(s) / grey braided cable^(el) / nickel base
 F10SLG / Ø 100 cm matt gold anodized / steel cable^(s) / gold braided cable^(el) / gold-plated base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	extra-low-voltage 12V DC LED	G4 bulb	12x1,5W 18W	1800	2700	85	A+	electronic 12V DC low voltage	YES Triac
			18x1,5W 27W	2700					
			24x1,5W 36W	3600					

weight: Ø 50 8 kg / Ø 70 10 kg / Ø 100 16 kg

p. 127



Fil de Fer Nuvola / pendant lamp

FNVAL / mod. A / aluminium / steel cables^(s) / grey braided cable^(el) / nickel base
 FNVEL / mod. E / aluminium / steel cables^(s) / grey braided cable^(el) / nickel base
 FNVFL / mod. F / aluminium / steel cables^(s) / grey braided cable^(el) / nickel base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	extra-low-voltage 12V DC LED	G4 bulb	24x1,5W 36W	3600	2700	85	A+	electronic 12V DC low voltage	YES Triac
			36x1,5W 54W	5400					
			44x1,5W 66W	6600					


Further dimensions and gold finish available on request.

Packaging included in the price for models A and E.

mod. A / 120x50x H 35 cm / base Ø 21x10,5 cm
 mod. E / 200x80x H 50 cm / base Ø 25x12,5 cm
 mod. F / 240x140x H 50 cm / base Ø 25x12,5 cm
 cables 170 cm to be cut to size



p. 130


**Fil de Fer Ovale** / pendant lamp

F7SVL / Ø 70 cm aluminium / steel cables^(s) / grey braided cable^(e) / nickel base
 F7SVLG / Ø 70 cm matt gold anodized / steel cables^(s) / gold braided cable^(e) / gold-plated base
 F11SVL / Ø 110 cm aluminium / steel cables^(s) / grey braided cable^(e) / nickel base
 F11SVLG / Ø 110 cm matt gold anodized / steel cables^(s) / gold braided cable^(e) / gold-plated base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	extra-low-voltage 12V DC LED	G4 bulb	20x1,5W 30W	3000	2700	85	A+	electronic 12V DC low voltage	YES Triac
			26x1,5W 39W	3900					

weight: Ø 70 8 kg / Ø 110 17 kg

p. 131


**Fil de Fer CW Ovale** / ceiling or wall lamp

F4PVL / Ø 45x25 cm aluminium / nickel base
 F4PVLG / Ø 45x25 cm matt gold anodized / gold-plated base
 F7PVL / Ø 70x30 cm aluminium / nickel base
 F7PVLG / Ø 70x30 cm matt gold anodized / gold-plated base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
220-240V	extra-low-voltage 12V DC LED	G4 bulb	8x1,5W 12W	1200	2700	85	A+	electronic 12V DC low voltage	YES Triac
			10x1,5W 15W	1500					

H ledge Ø 45: 25 cm / Ø 70: 30 cm

p. 133


**Fil de Fer F** / floor lamp

F3L / Ø 30 cm aluminium / grey braided cable / nickel dimmer
 F3LG / Ø 30 cm gold / gold braided cable / nickel dimmer
 F5L / Ø 50 cm aluminium / grey braided cable / nickel dimmer
 F5LG / Ø 50 cm gold / gold braided cable / nickel dimmer
 F7L / Ø 70 cm aluminium / grey braided cable / nickel dimmer
 F7LG / Ø 70 cm gold / gold braided cable / nickel dimmer
 F10L / Ø 100 cm aluminium / grey braided cable / nickel dimmer
 F10LG / Ø 100 cm gold / gold braided cable / nickel dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110V or 240V	extra-low-voltage 12V DC LED	G4 bulb	8x1,5W 12W	1200	2700	85	A+	low voltage plug driver	included (memory last step)
			10x1,5W 15W	1500					
			15x1,5W 22,5W	2250					
			20x1,5W 30W	3000					

12V cable: 170 cm / plug cable: 100 cm

p. 135

**Sweet Light Chandelier** / pendant lamp

CSL3QL / 3x Sweet Light Ø 10 cm / satin base 30x30 cm / H 180 cm
 CSL5QL / 5x Sweet Light Ø 10 cm / satin base 30x30 cm / H 180 cm
 CSL7CL / 7x Sweet Light Ø 10 cm / satin base Ø 40 cm / H 180 cm
 CSL7QL / 7x Sweet Light Ø 10 cm / satin base 60x60 cm / H 180 cm
 CSL10CL / 10x Sweet Light Ø 10 cm / satin base Ø 78 cm / H 180 cm
 CSL15QL / 15x Sweet Light Ø 10 cm / satin base 60x60 cm / H 300 cm
 CSL20CL / 20x Sweet Light Ø 10 cm / satin base Ø 78 cm / H 300 cm
 CSL35CL / 35x Sweet Light Ø 10 cm / satin base Ø 78 cm / H 400 cm


voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	extra-low-voltage 12V DC LED	G4 bulb	3x1,5W 4,5W	450	2700	85	A+	electronic 12V DC low voltage	YES Triac
			5x1,5W 7,5W	750					
			7x1,5W 10,5W	1050					
			10x1,5W 15W	1500					
			15x1,5W 22,5W	2250					
			20x1,5W 30W	3000					
			35x1,5W 52,2W	5250					

Standard version with aluminium Sweet Light spheres.

For further models see also PostKrisi Chandelier page 42.



p. 136

**Sweet Light T** / table lamp

SLL / Ø 10 cm aluminium / blue wire


SLLBR / Ø 10 cm brass / blue wire

SLLS / Ø 10 cm silver / blue wire

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
SLL / Ø 10 cm aluminium / blue wire SLLBR / Ø 10 cm brass / blue wire SLLS / Ø 10 cm silver / blue wire	110V-240V	extra low voltage 12V DC LED	G4 bulb	1x1,5W	150	2700	85	A+	low voltage plug driver	included touch (on the sphere)

cable: 250 cm

p. 137

**Uomo della Luce S** / table lamp

USL / rough iron structure / sphere Ø 10 cm aluminium / nickel/black dimmer / black wires


	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
USL / rough iron structure / sphere Ø 10 cm aluminium / nickel/black dimmer / black wires	110V-240V	extra low voltage 12V DC LED	G4 bulb	1x1,5W	150	2700	85	A+	low voltage plug driver	included (memory last step)

Lucenera

[*Finishes*] // **Nickel coating** (metal plating process) is chosen by the designer for its elegant and warm finish. To prevent any natural oxidation process, it requires regular cleaning. In alternative to nickel coating, customized finishes (i.e. chrome plating) can be provided upon request. / **Carbon and fiberglass tubes.** The production of the tubes is partially craftmade. Any imperfection in the texture is a peculiarity of the product and sign of craftsmanship. The quality of the tubes is guaranteed by using LED bulbs only, preferably with the max wattage included in our standard products.

[*Note*] // (*) LED bulbs can be dimmed using compatible dimmers, which have been tested specifically for dimming very low loads. The manufacturers of LED bulbs are required to draw up a list of suggested dimmers for the dimming of their products, with an indication of the maximum number of bulbs dimmable with the various types of dimmer.

p. 140

**Lucenera 200** / table lamp


L200L / black tube/base/flexible pipe / nickel stand and details

L200LW / white tube/base/flexible pipe / nickel stand and details

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
L200L / black tube/base/flexible pipe / nickel stand and details L200LW / white tube/base/flexible pipe / nickel stand and details	240V (110V available with on/off - bulb not supplied)	mains voltage LED	GU10 bulb	1x5,5W	375	3000	90	A+	-	included (memory 0%)



p. 141

**Lucenera 500 / table lamp**


L500L / black tube/base/stand / nickel details

L500LW / white tube/base/stand / nickel details

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
240V (110V available with on/off - bulb not supplied)	mains voltage LED	GU10 bulb	1x5,5W	375	3000	90	A+	-	included (memory 0%)



p. 143


**Lucenera 504 / pendant lamp**

L504L / black tube and base / metal braided cable / nickel details

L504LW / white tube and base / metal braided cable / nickel details

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulb not supplied)-240V	mains voltage LED	GU10 bulb	1x5,5W	375	3000	90	A+	-	YES IGBT/Triac*

p. 144-145

**Lucenera 502 / 503 / wall lamp**

L502L / Lucenera 502 / black tube/base/rod / nickel details

L502LW / Lucenera 502 / white tube/base/rod / nickel details


L503L / Lucenera 503 / black tubes/base/rods / nickel details

L503LW / Lucenera 503 / white tubes/base/rods / nickel details

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulb not supplied)-240V	mains voltage LED	GU10 bulb	1x5,5W	375	3000	90	A+	-	NO on/off switch included
110V (bulbs not supplied)-240V	mains voltage LED	GU10 bulb	2x5,5W 11W	750	3000	90	A+	-	NO on/off switch included

base 10x10x3,5 cm / H ledge 35/50 cm variable

p. 147

**Lucenera 506 / standing lamp**


L506L / black tube/base/stand / nickel details

L506LW / white tube/base/stand / nickel details

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110V (bulb not supplied)-240V	mains voltage LED	GU10 bulb	1x5,5W	375	3000	90	A+	-	included (memory last step)



p. 148




Lucenera 206 / ceiling lamp

L20680L / black tubes/base/flexible pipes / nickel details
L20680LW / white tubes/base/flexible pipes / nickel details

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
	110V (bulbs not supplied)-240V	mains voltage LED	GU10 bulb	2x5,5W 11W	750	3000	90	A+	-	YES IGBT/Triac*



p. 149




Lucenera 202 / wall lamp

L202L / black tube/base/flexible pipe / nickel details
L202LW / white tube/base/flexible pipe / nickel details

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
	110V (bulb not supplied)-240V	mains voltage LED	GU10 bulb	1x5,5W	375	3000	90	A+	-	YES IGBT/Triac*

p. 150




Lucenera 207 / standing lamp

L207L / black tube/base/flexible pipe / nickel stand and details
L207LW / white tube/base/flexible pipe / nickel stand and details

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
	110V (bulb not supplied)-240V	mains voltage LED	GU10 bulb	1x5,5W	375	3000	90	A+	-	included (memory last step)

p. 151



Lucenera 208 / standing lamp

L208L / black tubes/base/flexible pipes / nickel stands and details
L208LW / white tubes/base/flexible pipes / nickel stands and details

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
	110V (bulbs not supplied)-240V	mains voltage LED	GU10 bulb	2x5,5W 11W	750	3000	90	A+	-	included (memory last step)




Stchu-Moon

[*Finishes*] // **Rough iron** (untreated metal) is chosen by the designer specifically because of its uniqueness and its natural ageing property. The appearance of any uneven rust patches does not constitute a defect, since it is a typical sign of the ageing process, which might be considerably accelerated in conditions of high humidity or direct exposure to outdoor weathering. / **Nickel coating** (metal plating process) is chosen by the designer for its elegant and warm finish. To prevent any natural oxidation process, it requires regular cleaning. In alternative to nickel coating, customized finishes (i.e. chrome plating) can be provided upon request.

[*Note*] // (*) LED bulbs can be dimmed using compatible dimmers, which have been tested specifically for dimming very low loads. The manufacturers of LED bulbs are required to draw up a list of suggested dimmers for the dimming of their products, with an indication of the maximum number of bulbs dimmable with the various types of dimmer. / (**) The plug driver 110-240V is supplied with the electrical plug suitable for the market of reference only. Please specify in stage of order if the destination of the product differs from your standard.

[*Cables*] // (**s**) suspension cable. / (**el**) electrical cable.




Stchu-Moon 02 230V / pendant lamp

SM24230LS / Ø 40 cm silver (exterior black) / black cable / nickel base
 SM24230LG / Ø 40 cm gold (exterior black) / black cable / nickel base
 SM24230LC / Ø 40 cm copper (exterior black) / black cable / nickel base
 SM26230LS / Ø 60 cm silver (exterior black) / black cable / nickel base
 SM26230LG / Ø 60 cm gold (exterior black) / black cable / nickel base
 SM26230LC / Ø 60 cm copper (exterior black) / black cable / nickel base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulb not supplied)-240V	mains voltage LED	E27 bulb	1x8W	1055	2700	≥80	A++	-	YES IGBT/Triac*

Available on request with LED silver crowned bulb (code LLC31)

weight: Ø 40 cm 1,8 kg / Ø 60 cm 2,8 kg



Stchu-Moon 02 230V / pendant lamp


SM28230LS / Ø 80 cm silver (exterior black) / black cables / nickel base
 SM28230LG / Ø 80 cm gold (exterior black) / black cables / nickel base
 SM28230LC / Ø 80 cm copper (exterior black) / black cables / nickel base
 SM210230LS / Ø 100 cm silver (exterior black) / black cables / nickel base
 SM210230LG / Ø 100 cm gold (exterior black) / black cables / nickel base
 SM210230LC / Ø 100 cm copper (exterior black) / black cables / nickel base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulbs not supplied)-240V	mains voltage LED	E27 bulb	3x8W 24W	3165	2700	≥80	A++	-	YES IGBT/Triac*

Available on request with LED silver crowned bulbs (code LLC31)

weight: Ø 80 cm 6,5 kg / Ø 100 cm 7,5 kg

p. 155



Stchu-Moon 02 / pendant lamp


SM24LS / Ø 40 cm silver (exterior black) / steel spoons / black cable and base
 SM24LG / Ø 40 cm gold (exterior black) / steel spoons / black cable and base
 SM24LC / Ø 40 cm copper (exterior black) / steel spoons / black cable and base
 SM26LS / Ø 60 cm silver (exterior black) / steel spoons / black cable and base
 SM26LG / Ø 60 cm gold (exterior black) / steel spoons / black cable and base
 SM26LC / Ø 60 cm copper (exterior black) / steel spoons / black cable and base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
240V (110V available on request)	24V DC LED board	LED board	2x5W 10W	1000	2600-2800 perceived range	80	A	electronic 24V DC low voltage	YES Triac

weight: Ø 40 cm 2 kg / Ø 60 cm 3,5 kg



p. 155


**Stchu-Moon 02 / pendant lamp**

- SM28LS / Ø 80 cm silver (exterior black) / steel spoons / steel cable⁽⁶⁾ / black cable⁽⁶⁾ and base
- SM28LG / Ø 80 cm gold (exterior black) / steel spoons / steel cable⁽⁶⁾ / black cable⁽⁶⁾ and base
- SM28LC / Ø 80 cm copper (exterior black) / steel spoons / steel cable⁽⁶⁾ / black cable⁽⁶⁾ and base
- SM210LS / Ø 100 cm silver (exterior black) / steel spoons / steel cable⁽⁶⁾ / black cable⁽⁶⁾ and base
- SM210LG / Ø 100 cm gold (exterior black) / steel spoons / steel cable⁽⁶⁾ / black cable⁽⁶⁾ and base
- SM210LC / Ø 100 cm copper (exterior black) / steel spoons / steel cable⁽⁶⁾ / black cable⁽⁶⁾ and base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
240V (110V available on request)	24V DC LED board	LED board	4x5W 20W	2000	2600-2800 perceived range	80	A	electronic 24V DC low voltage	YES Triac

weight: Ø 80 cm 6,5 kg / Ø 100 cm 7,5 kg

p. 156


**Stchu-Moon 02 Chandelier / pendant lamp**

- SM234LS / Ø 40 cm silver (exterior black) / steel spoons / black cables and structure
- SM234LG / Ø 40 cm gold (exterior black) / steel spoons / black cables and structure
- SM234LC / Ø 40 cm copper (exterior black) / steel spoons / black cables and structure
- SM236LS / Ø 60 cm silver (exterior black) / steel spoons / black cables and structure
- SM236LG / Ø 60 cm gold (exterior black) / steel spoons / black cables and structure
- SM236LC / Ø 60 cm copper (exterior black) / steel spoons / black cables and structure

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
240V (110V available on request 1..10V or push dimm.)	24V DC LED board	LED board	6x5W 30W	3000	2600-2800 perceived range	80	A	electronic 24V DC low voltage	YES Triac

3x Ø 40 cm
H max 190 cm / tot. Ø 105 cm / weight 13,5 cm
3x Ø 60 cm
H max 200 cm / tot. Ø 145 cm / weight 18,5 cm

p. 159

**Stchu-Moon 05 / wall lamp**

- SM5LS / silver (exterior white) / steel spoon / white base
- SM5LG / gold (exterior white) / steel spoon / white base
- SM5LC / copper (exterior white) / steel spoon / white base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
240V (110V available on request 1..10V or push dimm.)	24V DC LED board	LED board	1x5W	500	2600-2800 perceived range	80	A	electronic 24V DC low voltage	YES Triac

p. 160

**Stchu-Moon 06 / wall lamp**


- SM6LS / silver (exterior black) / nickel flex and bulb cover / aluminium base
- SM6LG / gold (exterior black) / brass flex / nickel bulb cover / aluminium base
- SM6LC / copper (exterior black) / brass flex / nickel bulb cover / aluminium base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulb not supplied)-240V	mains voltage LED	E14 bulb	1x10W	800	2700	≥80	A+	-	YES IGBT/Triac*

H ledge 15/20 cm variable



p. 161

**Stchu-Moon R** / recessed lamp

SM114S / Ø 14 cm silver (bulb not included)

SM114G / Ø 14 cm gold (bulb not included)


SM114C / Ø 14 cm copper (bulb not included)

LS4 / LED bulb

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
-	mains voltage	GU10 bulb not included	-	-	-	-	-	-	-
220-240V	mains voltage LED	GU10 bulb	5,5W	375	3000	90	A+	-	YES IGBT/Triac*

installation hole Ø 13 cm / max depth 15 cm

p. 164

**Stchu-Moon 08** / wall/standing lamp

SM88LS / Ø 80 cm silver (exterior grey matt) / nickel light structure / black anvil

SM88LG / Ø 80 cm gold (exterior grey matt) / nickel light structure / black anvil

SM88LC / Ø 80 cm copper (exterior grey matt) / nickel light structure / black anvil


SM812LS / Ø 120 cm silver (exterior grey matt) / nickel light structure / black anvil

SM812LG / Ø 120 cm gold (exterior grey matt) / nickel light structure / black anvil

SM812LC / Ø 120 cm copper (exterior grey matt) / nickel light structure / black anvil

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
240V (110V available on request)	low voltage LED 12V	GU5.3 bulb	1x7W	630	3000	80	A+	-	included (memory 100%)

p. 165

**Stchu-Moon 09** / standing lamp


SM9LS / silver (rough iron ext.) / steel spoons / metal braided cable / black dimmer/cable

SM9LG / gold (rough iron ext.) / steel spoons / metal braided cable / black dimmer/cable

SM9LC / copper (rough iron ext.) / steel spoons / metal braided cable / black dimmer/cable

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110-240V	24V DC LED board (1x candle included)	LED board	2x5W 10W	1000	2600-2800 perceived range	80	A	low voltage plug driver**	included (memory last step)

p. 166

**Stchu-Moon 01** / floor lamp

SM14LS / Ø 40 cm silver (ext. black) / steel spoon / metal braided cable / black dimmer/cable

SM14LG / Ø 40 cm gold (ext. black) / steel spoon / metal braided cable / black dimmer/cable

SM14LC / Ø 40 cm copper (ext. black) / steel spoon / metal braided cable / black dimmer/cable

SM16LS / Ø 60 cm silver (ext. black) / steel spoons / metal braided cable / black dimmer/cable

SM16LG / Ø 60 cm gold (ext. black) / steel spoons / metal braided cable / black dimmer/cable

SM16LC / Ø 60 cm copper (ext. black) / steel spoons / metal braided cable / black dimmer/cable


voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110-240V	24V DC LED board	LED board	1x5W	500	2600-2800 perceived range	80	A	low voltage plug driver**	included (memory last step)
			2x5W 10W	1000					



Macchina della Luce


[*Finishes*] // **Nickel coating** (metal plating process) is chosen by the designer for its elegant and warm finish. To prevent any natural oxidation process, it requires regular cleaning. In alternative to nickel coating, customized finishes (i.e. chrome plating) can be provided upon request. / **Brass** (an alloy of copper and zinc) is a very elegant finish, yellow-gold in colour, with an excellent corrosion resistance. We use it untreated, therefore it may oxidise with time. Regular cleaning helps preserving its original appearance and slow down the ageing process, which might be anyway accelerated by the weather, frequent handling or conditions of high humidity.

[*Note*] // (*) LED bulbs can be dimmed using compatible dimmers, which have been tested specifically for dimming very low loads. The manufacturers of LED bulbs are required to draw up a list of suggested dimmers for the dimming of their products, with an indication of the maximum number of bulbs dimmable with the various types of dimmer.




Macchina della Luce mod. A / pendant lamp	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
MALG / discs Ø 80-50-30-18 cm / gold / nickel base / brass rods	220-240V	24V DC LED board	LED board	7x6W 42W	4410	2600-2800 perceived range	80	A+	electronic 24V DC low voltage	YES Triac
MALS / discs Ø 80-50-30-18 cm / silver / nickel base / aluminium rods										
MALC / discs Ø 80-50-30-18 cm / copper / nickel base / brass rods										
MALG110V / discs Ø 80-50-30-18 cm / gold / nickel base / brass rods	110V	24V DC LED board	LED board	7x6W 42W	4410	2600-2800 perceived range	80	A+	electronic 24V DC low voltage	YES Triac
MALS110V / discs Ø 80-50-30-18 cm / silver / nickel base / aluminium rods										
MALC110V / discs Ø 80-50-30-18 cm / copper / nickel base / brass rods										

weight 10 kg / rods 300 cm available on request



Macchina della Luce mod. B / pendant lamp	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
MBLG / discs Ø 80-18 cm / gold / nickel base / brass rods	220-240V	24V DC LED board	LED board	2x6W 12W	1260	2600-2800 perceived range	80	A+	electronic 24V DC low voltage	YES Triac
MBSL / discs Ø 80-18 cm / silver / nickel base / aluminium rods										
MBLC / discs Ø 80-18 cm / copper / nickel base / brass rods										
MBLG110V / discs Ø 80-18 cm / gold / nickel base / brass rods	110V	24V DC LED board	LED board	2x6W 12W	1260	2600-2800 perceived range	80	A+	electronic 24V DC low voltage	YES Triac
MBSL110V / discs Ø 80-18 cm / silver / nickel base / aluminium rods										
MBLC110V / discs Ø 80-18 cm / copper / nickel base / brass rods										

weight 6 kg / rods 300 cm available on request




Macchina della Luce mod. C / pendant lamp	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
MCLG / discs Ø 120 (flying leaf)-80-50 cm / gold / nickel base / brass rods	220-240V	24V DC LED board	LED board	7x6W 42W	4410	2600-2800 perceived range	80	A+	electronic 24V DC low voltage	YES Triac
MCLS / discs Ø 120 (flying leaf)-80-50 cm / silver / nickel base / aluminium rods										
MCLC / discs Ø 120 (flying leaf)-80-50 cm / copper / nickel base / brass rods										
MCLG110V / discs Ø 120 (flying leaf)-80-50 cm / gold / nickel base / brass rods	110V	24V DC LED board	LED board	7x6W 42W	4410	2600-2800 perceived range	80	A+	electronic 24V DC low voltage	YES Triac
MCLS110V / discs Ø 120 (flying leaf)-80-50 cm / silver / nickel base / aluminium rods										
MCLC110V / discs Ø 120 (flying leaf)-80-50 cm / copper / nickel base / brass rods										

weight 13 kg / rods 300 cm available on request



p. 171

**Macchina della Luce mod. D / pendant lamp**

MDLG / discs Ø 120 (flying leaf)-80-50-30-18 cm / gold / nickel base / brass rods

MDLS / discs Ø 120 (flying leaf)-80-50-30-18 cm / silver / nickel base / aluminium rods

MDLC / discs Ø 120 (flying leaf)-80-50-30-18 cm / copper / nickel base / brass rods


MDLG110V / discs Ø 120 (flying leaf)-80-50-30-18 cm / gold / nickel base / brass rods

MDLS110V / discs Ø 120 (flying leaf)-80-50-30-18 cm / silver / nickel base / aluminium rods

MDLC110V / discs Ø 120 (flying leaf)-80-50-30-18 cm / copper / nickel base / brass rods

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
220-240V	24V DC LED board	LED board	10x6W 60W	6300	2600-2800 perceived range	80	A+	electronic 24V DC low voltage	YES Triac
110V	24V DC LED board	LED board	8x6W 48W	5040	2600-2800 perceived range	80	A+	electronic 24V DC low voltage	YES Triac

weight 16 kg / rods 300 cm available on request

**Macchina della Luce mod. E / pendant lamp**

MELG / discs Ø 50-30-18 cm / gold / nickel base / brass rods

MELS / discs Ø 50-30-18 cm / silver / nickel base / aluminium rods

MELC / discs Ø 50-30-18 cm / copper / nickel base / brass rods


MELG110V / discs Ø 50-30-18 cm / gold / nickel base / brass rods

MELS110V / discs Ø 50-30-18 cm / silver / nickel base / aluminium rods

MELC110V / discs Ø 50-30-18 cm / copper / nickel base / brass rods

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
220-240V	24V DC LED board	LED board	4x6W 24W	2520	2600-2800 perceived range	80	A+	electronic 24V DC low voltage	YES Triac
110V	24V DC LED board	LED board	4x6W 24W	2520	2600-2800 perceived range	80	A+	electronic 24V DC low voltage	YES Triac

weight 6 kg / rods 300 cm available on request

**Macchina della Luce mod. F / pendant lamp**

MFLG / discs Ø 120 (flying leaf)-80-50-30 cm / gold / nickel base / brass rods

MFLS / discs Ø 120 (flying leaf)-80-50-30 cm / silver / nickel base / aluminium rods

MFLC / discs Ø 120 (flying leaf)-80-50-30 cm / copper / nickel base / brass rods

MFLG110V / discs Ø 120 (flying leaf)-80-50-30 cm / gold / nickel base / brass rods


MFLS110V / discs Ø 120 (flying leaf)-80-50-30 cm / silver / nickel base / aluminium rods

MFLC110V / discs Ø 120 (flying leaf)-80-50-30 cm / copper / nickel base / brass rods

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
220-240V	24V DC LED board	LED board	9x6W 54W	5670	2600-2800 perceived range	80	A+	electronic 24V DC low voltage	YES Triac
110V	24V DC LED board	LED board	8x6W 48W	5040	2600-2800 perceived range	80	A+	electronic 24V DC low voltage	YES Triac

weight 15 kg / rods 300 cm available on request

p. 172

**Macchina della Luce mod. I / pendant lamp**

MILG / discs Ø 80-50-30 cm / gold / nickel base / brass rods

MILS / discs Ø 80-50-30 cm / silver / nickel base / aluminium rods

MILC / discs Ø 80-50-30 cm / copper / nickel base / brass rods

MILG110V / discs Ø 80-50-30 cm / gold / nickel base / brass rods

MILS110V / discs Ø 80-50-30 cm / silver / nickel base / aluminium rods


MILC110V / discs Ø 80-50-30 cm / copper / nickel base / brass rods

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
220-240V	24V DC LED board	LED board	5x6W 30W	3150	2600-2800 perceived range	80	A+	electronic 24V DC low voltage	YES Triac
110V	24V DC LED board	LED board	5x6W 30W	3150	2600-2800 perceived range	80	A+	electronic 24V DC low voltage	YES Triac

weight 8 kg / rods 300 cm available on request



p. 175

**Macchina della Luce W mod. I** / wall lamp

MPILW / discs Ø 80-50-30 cm / white / white base

MPILG / discs Ø 80-50-30 cm / gold / gold base

MPILS / discs Ø 80-50-30 cm / silver / silver base

MPILC / discs Ø 80-50-30 cm / copper / copper base



	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
MPILW / discs Ø 80-50-30 cm / white / white base	110V (bulbs not supplied)-240V	mains voltage LED	G9 bulbs	8x3,5W 28W	2080	2700	>80	A+	-	YES IGBT/Triac
MPILG / discs Ø 80-50-30 cm / gold / gold base										
MPILS / discs Ø 80-50-30 cm / silver / silver base										
MPILC / discs Ø 80-50-30 cm / copper / copper base										


Macchina della Luce W mod. C / wall lamp

MPCLW / discs Ø 120-80-50 cm / white / white base

MPCLG / discs Ø 120-80-50 cm / gold / gold base

MPCLS / discs Ø 120-80-50 cm / silver / silver base

MPCLC / discs Ø 120-80-50 cm / copper / copper base




	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
MPCLW / discs Ø 120-80-50 cm / white / white base	110V (bulbs not supplied)-240V	mains voltage LED	G9 bulbs	8x3,5W 28W	2080	2200	>80	A+	-	YES IGBT/Triac*
MPCLG / discs Ø 120-80-50 cm / gold / gold base										
MPCLS / discs Ø 120-80-50 cm / silver / silver base										
MPCLC / discs Ø 120-80-50 cm / copper / copper base										

Luci d'Oro

[*Finishes*] // **Nickel coating** (metal plating process) is chosen by the designer for its elegant and warm finish. To prevent any natural oxidation process, it requires regular cleaning. In alternative to nickel coating, customized finishes (i.e. chrome plating) can be provided upon request. / **Brass** (an alloy of copper and zinc) is a very elegant finish, yellow-gold in colour, with an excellent corrosion resistance. We use it untreated, therefore it may oxidise with time. Regular cleaning helps preserving its original appearance and slow down the ageing process, which might be anyway accelerated by the weather, frequent handling or conditions of high humidity. / **Rough iron** (untreated metal) is chosen by the designer specifically because of its uniqueness and its natural ageing property. The appearance of any uneven rust patches does not constitute a defect, since it is a typical sign of the ageing process, which might be considerably accelerated in conditions of high humidity or direct exposure to outdoor weathering.

[*Note*] // (*) LED bulbs can be dimmed using compatible dimmers, which have been tested specifically for dimming very low loads. The manufacturers of LED bulbs are required to draw up a list of suggested dimmers for the dimming of their products, with an indication of the maximum number of bulbs dimmable with the various types of dimmer. / (**) Our LEDs can be dimmed by using compatible dimmers tested specifically to dim very low loads. We suggest checking the minimum load of the dimmer before installation.

p. 179

**Malagola 27** / pendant lamp

ML27LG / gold / black base and cable

ML27LS / silver / black base and cable


ML27LC / copper / black base and cable

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
ML27LG / gold / black base and cable	110V-240V	constant current LED	COB LED	1x2W	300	2700	≥80	A++	constant current driver	NO
ML27LS / silver / black base and cable										
ML27LC / copper / black base and cable										

weight 0,9 kg



p. 179

**Malagola 55 / pendant lamp**

ML55LG / gold / black-cloth cable / black base


ML55LS / silver / black-cloth cable / black base

ML55LC / copper / black-cloth cable / black base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulb not supplied)-240V	mains voltage LED	E27 bulb	1x8W	1055	2700	≥80	A++	-	YES IGBT/Triac*

weight 1,7 kg

p. 179

**Malagola 110 / pendant lamp**


ML110LG / gold / black-cloth cable / black base

ML110LS / silver / black-cloth cable / black base

ML110LC / copper / black-cloth cable / black base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulbs not supplied)-240V	mains voltage LED	E27 bulb	3x8W 24W	3165	2700	≥80	A++	-	YES IGBT/Triac*

weight 4,5 kg

**Gold Moon JC / IC / pendant lamp**


GMJC / mod. JC / nickel jack connection / black wire / black/gold wrap shade / copper curl

GMIC / mod. IC / nickel plate with tensioner / black wire / black/gold wrap shade / copper curl

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
-	constant current LED 350 mA	LED Jack/interch. interch. LED	1x1W	100	2700	80	A+	not included available on request	-

*Available in a minimum amount of 20 pieces (not available as single pendant)*installation hole mod. JC Ø 1,3 cm
installation hole mod. IC Ø 5,5 cm

p. 180

**Gold Moon Chandelier / pendant lamp**

CGM20CL / satin steel base / 20x black/gold wrap shades / copper curls / nickel jack / black wires

CGM25CL / satin steel base / 25x black/gold wrap shades / copper curls / nickel jack / black wires


CGM35CL / satin steel base / 35x black/gold wrap shades / copper curls / nickel jack / black wires

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	constant current LED 350 mA	interch. LED	20x1W 20W 25x1W 25W 35x1W 35W	2000 2500 3500	2700	80	A+	constant current driver	YES IGBT/Triac

*Available with different base dimensions and pendants amount (minimum 20)*base Ø 78 cm / shades Ø 20 cm ca. /
H max 300 cm not adjustable



p. 185


**DiscO** / ceiling lamp

DSOLG / gold / polished aluminium and nickel details
 DSOLS / silver / polished aluminium and nickel details
 DSOLC / copper / polished aluminium and nickel details
 DSOLW / white / polished aluminium and nickel details

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
240V (available 110V DALI dimmable)	constant current LED	COB LED	1x15W	2200	2700	80	A++	constant current LED driver	YES Triac



p. 186

**Telchisugiò** / wall lamp

TCSLG / gold / brass flex / aluminium base
 TCCLS / silver / nickel flex / aluminium base
 TCCLC / copper / brass flex / aluminium base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
220-240V (110V available on request)	low voltage LED	GU4 bulb	1x3,5W	140	2700	80	A	low voltage driver	NO

flex Ø 0,6x40 cm


p. 187

**Luna W** / wall lamp

LNW30G / gold / copper stick / brass flex
 LNW30S / silver / copper stick / brass flex
 LNW30C / copper / copper stick / brass flex

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V or 240V	constant current LED 350 mA	interch. LED	2x1W 2W	200	2700	80	A+	constant current driver	NO

p. 189

**Luna Piena 80 / 120** / ceiling or wall lamp

LP80LG / Luna Piena 80 / gold flying leaf (exterior grey matt) / brass flex / white base
 LP80LS / Luna Piena 80 / silver flying leaf (exterior grey matt) / nickel flex / white base
 LP80LC / Luna Piena 80 / copper flying leaf (exterior grey matt) / brass flex / white base
 LP120LG / Luna Piena 120 / gold flying leaf (exterior grey matt) / brass flex / white base
 LP120LS / Luna Piena 120 / silver flying leaf (exterior grey matt) / nickel flex / white base
 LP120LC / Luna Piena 120 / copper flying leaf (exterior grey matt) / brass flex / white base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
220-240V (110V available on request)	low voltage LED 12V	GU5.3	1x7W	630	3000	80	A+	low voltage driver	YES IGBT/Triac

Ø 80: flex Ø 1,3x50 cm
 Ø 120: flex Ø 1,5x80 cm



p. 190



Ø 50/80/120 cm


Full Moon 50 / 80 / 120 / wall lamp

FM50W / Full Moon 50 / white / nickel sticks / white base
 FM50G / Full Moon 50 / gold / nickel sticks / white base
 FM50S / Full Moon 50 / silver / nickel sticks / white base
 FM80W / Full Moon 80 / white / nickel sticks / white base
 FM80G / Full Moon 80 / gold / nickel sticks / white base
 FM80S / Full Moon 80 / silver / nickel sticks / white base
 FM120W / Full Moon 120 / white / nickel sticks / white base
 FM120G / Full Moon 120 / gold / nickel sticks / white base
 FM120S / Full Moon 120 / silver / nickel sticks / white base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
240V (110V available not dimmable)	constant current LED 350 mA	interch. LED	5x1W 5W	500	2700	80	A+	constant current driver	YES IGBT/Triac**
240V (110V available 1 ... 10V or push dimmable)			10x1W 10W	1000					

base Ø 9x3 cm

p. 191




Ø 80/120 cm 12 cm ca.

Francesca 80 / 120 / wall lamp

FR8LWG / Francesca 80 / white/gold back side / white base
 FR8LG / Francesca 80 / gold / gold base
 FR8LS / Francesca 80 / silver / silver base
 FR8LC / Francesca 80 / copper / copper base
 FR12LWG / Francesca 120 / white/gold back side / white base
 FR12LG / Francesca 120 / gold / gold base
 FR12LS / Francesca 120 / silver / silver base
 FR12LC / Francesca 120 / copper / copper base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulbs not supplied)-240V	mains voltage LED	G9 bulb	4x3,5W 14W	1040	2700	>80	A+	-	YES IGBT/Triac*


p. 192

**Luce d'Oro T / table lamp**

LOLG / gold / brass flex / rough iron base / black switch and cable
 LOLS / silver / nickel flex / rough iron base / black switch and cable
 LOLC / copper / brass flex / rough iron base / black switch and cable

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110V or 240V	low voltage LED 12V	GU4 bulb	1x3,5W	140	2700	80	A	-	NO on/off switch included

p. 193


**Luce d'Oro F / standing lamp**

LOFLG / gold / brass flex / rough iron base and structure / black cable and dimmer
 LOFLS / silver / nickel flex / rough iron base and structure / black cable and dimmer
 LOFLC / copper / brass flex / rough iron base and structure / black cable and dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
240V (110V available on request)	low voltage LED 12V	GU5.3 bulb	1x7W	630	3000	80	A+	-	included (memory 100%)



p. 194

**Luna** / table candle holder


LNG / gold / rough iron base

LNS / silver / rough iron base

LNC / copper / rough iron base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
-	candle (included)	-	-	-	-	-	-	-	-

p. 195

**Gemma** / table candle holder


GMG / gold / rough iron structure

GMS / disc silver / rough iron structure

GMC / copper / rough iron structure

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
-	candle (included)	-	-	-	-	-	-	-	-

p. 196

**Colonna** / standing lamp


CNLG / gold interior (flying leaf) / rough iron coloumn / black dimmer

CNLS / silver interior (flying leaf) / rough iron coloumn / black dimmer

CNLC / copper interior (flying leaf) / rough iron coloumn / black dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110V (bulb not supplied)-240V	mains voltage LED	E27 bulb	1x17W	1900	2700	80	A+	-	included (memory last step)

p. 197

**Pepita 1 / 2** / recessed lamp

P1W / Pepita 1 / white shade Ø 8 cm / plasterboard panel 22x20 cm included

P1G / Pepita 1 / gold shade Ø 8 cm / plasterboard panel 22x20 cm included

P1S / Pepita 1 / silver shade Ø 8 cm / plasterboard panel 22x20 cm included

P2W / Pepita 2 / white shade Ø 14 cm / plasterboard panel 30x30 cm included

P2G / Pepita 2 / gold shade Ø 14 cm / plasterboard panel 30x30 cm included

P2S / Pepita 2 / silver shade Ø 14 cm / plasterboard panel 30x30 cm included

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
-	constant current LED 350 mA	LED Jack	1x1W	100	2700	80	A+	not included available on request	-
			2x1W 2W	200					




Turciù

[*Finishes*] // **Nickel coating** (metal plating process) is chosen by the designer for its elegant and warm finish. To prevent any natural oxidation process, it requires regular cleaning. In alternative to nickel coating, customized finishes (i.e. chrome plating) can be provided upon request. / **Brass** (an alloy of copper and zinc) is a very elegant finish, yellow-gold in colour, with an excellent corrosion resistance. We use it untreated, therefore it may oxidise with time. Regular cleaning helps preserving its original appearance and slow down the ageing process, which might be anyway accelerated by the weather, frequent handling or conditions of high humidity. / **Rough iron** (untreated metal) is chosen by the designer specifically because of its uniqueness and its natural ageing property. The appearance of any uneven rust patches does not constitute a defect, since it is a typical sign of the ageing process, which might be considerably accelerated in conditions of high humidity or direct exposure to outdoor weathering.

[*Note*] // (*) LED bulbs can be dimmed using compatible dimmers, which have been tested specifically for dimming very low loads. The manufacturers of LED bulbs are required to draw up a list of suggested dimmers for the dimming of their products, with an indication of the maximum number of bulbs dimmable with the various types of dimmer. / (**) Halogen version available until exhaustion of bulbs stock.

p. 201




Turciù 36 / ceiling/pendant lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
TRS36NC / nickel flex (nickel lampholder) / satin nickel base	110V (bulbs not supplied)-240V	mains voltage halogen**	E14 bulb	36x20W 720W	8460	2700	100	D	-	YES IGBT/Triac*
TRS36BR / brass flex (nickel lampholder) / satin nickel base										
TRS36LNC / nickel flex (nickel lampholder) / satin nickel base										
TRS36LBR / brass flex (nickel lampholder) / satin nickel base										

flex Ø 0,85 cm:
7x75 cm / 10x100 cm / 9x125 cm / 10x150 cm
weight 20 kg

p. 201




Turciù 21 / ceiling/pendant lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
TRS21NC / nickel flex (nickel lampholder) / satin nickel base	110V (bulbs not supplied)-240V	mains voltage halogen**	E14 bulb	21x20W 420W	4935	2700	100	D	-	YES IGBT/Triac*
TRS21BR / brass flex (nickel lampholder) / satin nickel base										
TRS21LNC / nickel flex (nickel lampholder) / satin nickel base										
TRS21LBR / brass flex (nickel lampholder) / satin nickel base										

flex Ø 0,85 cm: 5x100 cm / 16x150 cm
weight 11 kg


p. 201



Turciù 16 / ceiling/pendant lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
TRS16NC / nickel flex (nickel lampholder) / satin nickel base	110V (bulbs not supplied)-240V	mains voltage halogen**	E14 bulb	16x20W 320W	3760	2700	100	D	-	YES IGBT/Triac*
TRS16BR / brass flex (nickel lampholder) / satin nickel base										
TRS16LNC / nickel flex (nickel lampholder) / satin nickel base										
TRS16LBR / brass flex (nickel lampholder) / satin nickel base										

flex Ø 0,85 cm: 16x150 cm
weight 9 kg


**Turciù 9 / ceiling/pendant lamp**

- TRS9NC / nickel flex (nickel lampholder) / satin nickel base
- TRS9BR / brass flex (nickel lampholder) / satin nickel base
- TRS9LNC / nickel flex (nickel lampholder) / satin nickel base
- TRS9LBR / brass flex (nickel lampholder) / satin nickel base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulbs not supplied)-240V	mains voltage halogen**	E14 bulb	9x20W 180W	2115	2700	100	D	-	YES IGBT/Triac*
	mains voltage LED		9x4W 36W	3240		≥80	A+		

flex Ø 0,85 cm: 9x150 cm
weight 5 kg

p. 202


**Turciù 9 / wall lamp**

- TR9NC / nickel flex (nickel lampholder) / satin nickel base
- TR9BR / brass flex (nickel lampholder) / satin nickel base
- TR9LNC / nickel flex (nickel lampholder) / satin nickel base
- TR9LBR / brass flex (nickel lampholder) / satin nickel base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulbs not supplied)-240V	mains voltage halogen**	E14 bulb	9x20W 180W	2115	2700	100	D	-	YES IGBT/Triac*
	mains voltage LED		9x4W 36W	3240		≥80	A+		

flex Ø 0,85 cm: 9x75 cm

p. 203


**Turciù 5 / wall lamp**

- TR5NC / nickel flex (nickel lampholder) / nickel base
- TR5BR / brass flex (nickel lampholder) / nickel base
- TR5LNC / nickel flex (nickel lampholder) / nickel base
- TR5LBR / brass flex (nickel lampholder) / nickel base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulbs not supplied)-240V	mains voltage halogen**	E14 bulb	5x20W 100W	1175	2700	100	D	-	YES IGBT/Triac*
	mains voltage LED		5x4W 20W	1800		≥80	A+		

flex Ø 0,85 cm: 5x75 cm

p. 204

**Turciù 3 / 2 / wall lamp**

- TR3NC / Turciù 3 / halogen / nickel flex (nickel lampholder) / nickel base
- TR3BR / Turciù 3 / halogen / brass flex (nickel lampholder) / nickel base
- TR3LNC / Turciù 3 / LED / nickel flex (nickel lampholder) / nickel base
- TR3LBR / Turciù 3 / LED / brass flex (nickel lampholder) / nickel base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulbs not supplied)-240V	mains voltage halogen**	E14 bulb	3x20W 60W	705	2700	100	D	-	YES IGBT/Triac*
	mains voltage LED		3x4W 12W	1080		≥80	A+		




- TR2NC / Turciù 2 / halogen / nickel flex (nickel lampholder) / nickel base
- TR2BR / Turciù 2 / halogen / brass flex (nickel lampholder) / nickel base
- TR2LNC / Turciù 2 / LED / nickel flex (nickel lampholder) / nickel base
- TR2LBR / Turciù 2 / LED / brass flex (nickel lampholder) / nickel base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110V (bulbs not supplied)-240V	mains voltage halogen**	E14 bulb	2x20W 40W	470	2700	100	D	-	YES IGBT/Triac*
	mains voltage LED		2x4W 8W	720		≥80	A+		

flex Ø 1,3 cm: 3/2x50 cm
on request available with flex Ø 0,85 cm




p. 205

**Bonsai** / table lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
BNBR / halogen / brass flex (nickel lampholder) / iron base / black cable and dimmer	240V (110V available on request / bulbs not supplied)	mains voltage halogen	E14 bulb	12x15W 180W	1320	-	-	E	-	included
BNLBR / LED / brass flex (nickel lampholder) / iron base / black cable and dimmer		mains voltage LED		12x2,7W 32,4W	1800	2700	≥80	A+		

flex Ø 0,6 cm: 12x60 cm


p. 206

**Sottovento 15 / 16** / standing lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
SVLNC / Sottovento 15 / nickel flex (nickel lampholder) / iron structure / black cable and dimmer	240V (110V available on request / bulbs not supplied)	mains voltage LED	E14 bulb	15x4W 60W	5400	2700	≥80	A+	-	included
SVLBR / Sottovento 15 / brass flex (nickel lampholder) / iron structure / black cable and dimmer										
SVNC / Sottovento 16 / nickel flex (nickel lampholder) / iron structure / black cable and dimmer	240V (110V available on request / bulbs not supplied)	mains voltage halogen**	E14 bulb	16x20W 320W	3760	2700	100	D	-	included
SVBR / Sottovento 16 / brass flex (nickel lampholder) / iron structure / black cable and dimmer										

Sottovento 16: base 30x30 cm / flex Ø 0,85 16x150 cm
Sottovento 15: base 40x40 cm / flex Ø 1,2 15x150 cm

p. 207

**Albero della Luce** / standing lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
ALLBR / brass flex (nickel lampholder) / iron structure / black cable	240V (110V available on request / bulbs not supplied)	mains voltage LED	E14 bulb	36x4W 144W	12960	2700	≥80	A+	-	wireless (remote control included)

flex Ø 0,85 cm: 36x150 cm



Oggetti Senza Tempo

[*Finishes*] // **Nickel coating** (metal plating process) is chosen by the designer for its elegant and warm finish. To prevent any natural oxidation process, it requires regular cleaning. In alternative to nickel coating, customized finishes (i.e. chrome plating) can be provided upon request. / **Brass** (an alloy of copper and zinc) is a very elegant finish, yellow-gold in colour, with an excellent corrosion resistance. We use it untreated, therefore it may oxidise with time. Regular cleaning helps preserving its original appearance and slow down the ageing process, which might be anyway accelerated by the weather, frequent handling or conditions of high humidity. / **Copper** is a very malleable and ductile metal, chosen for its high thermal and electrical conductivity, as well as for its typical reddish-orange colour. We use it untreated, therefore it may oxidise with time, forming a green patina. Regular cleaning helps preserving its original appearance and slow down the ageing process, which might be anyway accelerated by the weather, frequent handling or conditions of high humidity.

[*Note*] // (*) LED bulbs can be dimmed using compatible dimmers, which have been tested specifically for dimming very low loads. The manufacturers of LED bulbs are required to draw up a list of suggested dimmers for the dimming of their products, with an indication of the maximum number of bulbs dimmable with the various types of dimmer. / (**) The plug driver 110-240V is supplied with the electrical plug suitable for the market of reference only. Please specify in stage of order if the destination of the product differs from your standard.

p. 211



EC 301 / wall or ceiling lamp

EC301JB / black structure and base / brass joint and lens holder / glass lens
 EC301JW / white structure and base / brass joint and lens holder / glass lens

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
220-240V	constant current LED 500 mA	COB LED	1x5W 5W	600	2700	80	A++	constant current driver	YES IGBT/Triac*

p. 215




Herem T / USB table lamp

HRT / brass flex and shade

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
110-240V	constant voltage LED 5V	LED board	1x2,2W	160	3000	70	A+	USB plug driver 5V (EU plug only)	included touch-less

p. 216




CicloItalia T / table lamp

CIBR / brass base and structure / brass/black dimmer / black wire

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110-240V	constant current LED 500 mA	COB LED	1x5W	600	2700	80	A++	plug driver**	included (memory last step)




p. 218

**CicloItalia F** / standing lamp

CIFBR / black base / brass structure / black wire
 CIFBRM / black base / brass structure / black dimmer and wire

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
CIFBR / black base / brass structure / black wire	220-240V	constant current LED 500 mA	COB LED	1x5W	600	2700	80	A++	plug driver (EU plug only)	included touch (memory 0%)
CIFBRM / black base / brass structure / black dimmer and wire	110-240V								plug driver**	included (memory last step)


p. 223

**Lola T** / table lamp

LBR / brass structure / copper stick / black wire / brass/black dimmer

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
LBR / brass structure / copper stick / black wire / brass/black dimmer	110-240V	constant current LED 350 mA	interch. LED	3x1W 3W	300	2700	80	A+	plug driver**	included (memory last step)


p. 225

**Lola F** / standing lamp

LFBR / brass structure / copper stick / black wire
 LFBRM / brass structure / copper stick / black dimmer and wire

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
LFBR / brass structure / copper stick / black wire	220-240V	constant current LED 350 mA	interch. LED	3x1W 3W	300	2700	80	A+	plug driver (EU plug only)	included touch (memory 0%)
LFBRM / brass structure / copper stick / black dimmer and wire	110-240V								plug driver**	included (memory last step)

p. 226

**Ametista** / recessed lamp


AMI / nickel / nickel stick

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
AMI / nickel / nickel stick	-	constant current LED 350 mA	interch. LED	1x1W	100	2700	80	A+	not included available on request	-

installation hole Ø 13 cm / max depth 7 cm



p. 229




50x50 cm

Luce che dipinge / wall lamp

LD5L / white canvas / black pipe / black wrap screen

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
240V (110V available on request)	extra-low-voltage 12V DC LED bulb	G4	1x1,5W	150	2700	85	A+	low voltage driver	NO

p. 230




30 cm variable

Miracolo / table candle holder

MRBR / brass flex and details

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
-	candle (included)	-	-	-	-	-	-	-	-

p. 231



55 cm variable

11x9 cm


Nike / table lamp

NKL / white ceramic chalk statue / nickel flex / glass lens / blue wire / nickel/black dimmer

NKLPL / white ceramic chalk statue / nickel flex / glass lens / blue wire / nickel/black dimmer

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
220-240V (EU plug only)	constant current LED 350 mA	interch. LED	1x1W	100	2700	80	A+	constant current plug driver (EU plug only)	included (memory 100%)
110-240V (all other plugs)	constant current LED 350 mA	interch. LED	1x1W	100	2700	80	A+	constant current plug driver (all other plugs)**	included (memory last step)

p. 232



50x50 cm

150 cm

10x10 cm

Shadow / standing lamp with net

SW / black structure / brass net / black wire and dimmer


voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110-240V	constant current LED 350 mA	interch. LED	1x1W	100	2700	80	A+	constant current plug driver**	included (memory last step)



Medousê (outdoor)

[Note] // (*) Mains voltage LED modules and COB LED are dimmable using IGBT (trailing edge) dimmers designed specifically for LED sources. Their dimming is extremely delicate: incompatible dimmers may cause irreparable damage to the LED. Some dimmers on the market have a NO button (Normally Open) or are specific connector socket-mounted or recessed. They are generally inserted into junction boxes; their limited thickness facilitates the installer's task and makes the dimmer fit for installation even in shallow boxes. Dimmers with an integrated radio dimmer for both manual (NO button) and wireless control are also available. It is important to note that during adjustment the dimming appears less precise, with some flickering. Furthermore some types of dimmer, even if they have been recommended by the manufacturers themselves, have visible flickering (almost essentially down to a minimum) depending on the mains and on the type of interference present. The problem can be solved by increasing the minimum value setting of the potentiometer on the dimmer.

p. 239



Medousê W / wall lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
MD3P / green glass / brass rod	110V or 240V	mains voltage LED	LED module IP64	1x17W	1650	2700	80	A+	-	YES*
MD3PTR / transparent glass / brass rod										

p. 240



Medousê F / floor lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
MD3 / Ø 30 cm / green glass / aluminium details / plug cable (code MDCV) not included	110V or 240V	mains voltage LED	LED module IP64	1x29W	2580	2700	80	A+	-	YES*
MD3TR / Ø 30 cm / transparent glass / brass details / plug cable (code MDCV) not included										
MD5 / Ø 50 cm / green glass / aluminium details / plug cable (code MDCV) not included										
MD5TR / Ø 50 cm / transparent glass / brass details / plug cable (code MDCV) not included										

weight: Ø 30 cm 15 kg / Ø 50 cm 31 kg




More (outdoor)

[*Finishes*] // **Zinc plated metal** is the material of the stems of the More collection. They are suitable for outdoor installation, but they are not immersion proof. On request we can supply stems suitable for this kind of installation into water.

[*Cables*] // **(s)** suspension cable. / **(el)** electrical cable.

[*Note*] // **(*)** IP specifics: lampholder IP65 (not protected against immersion); wires and connectors IP68; drivers IP67; IP average rate of the lamp 44.

p. 244



More / pendant lamp / driver and accessories not incl. (see pages 106-111)

MRS / transparent glass / steel cable^(s) / grey-transparent cable^(el)


MRSA / amber glass / steel cable^(s) / grey-transparent cable^(el)

MRSGR / green glass / steel cable^(s) / grey-transparent cable^(el)

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
-	extra-low-voltage 12V DC LED bulb	G4 bulb (IP65 lampholder)*	1x1,5W	150	2700	85	A+	not included available on request	-

weight 1 kg

p. 247



More 0 / floor lamp / driver and accessories not incl. (see pages 106-111)


MR0 / transparent glass / grey-transparent cable 300 cm

MR0A / amber glass / grey-transparent cable 300 cm

MR0GR / green glass / grey-transparent cable 300 cm

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
-	extra-low-voltage 12V DC LED bulb	G4 bulb (IP65 lampholder)*	1x1,5W	150	2700	85	A+	not included available on request	-

p. 248



More F / standing lamp / driver and accessories not incl. (see pages 106-111)

MR70 / H 70 cm / metal stem / transparent glass / grey-transparent cable 210 cm

MR70A / H 70 cm / metal stem / amber glass / grey-transparent cable 210 cm

MR70GR / H 70 cm / metal stem / green glass / grey-transparent cable 210 cm

MR100 / H 100 cm / metal stem / transparent glass / grey-transparent cable 170 cm

MR100A / H 100 cm / metal stem / amber glass / grey-transparent cable 170 cm

MR100GR / H 100 cm / metal stem / green glass / grey-transparent cable 170 cm

MR130 / H 130 cm / metal stem / transparent glass / grey-transparent cable 150 cm

MR130A / H 130 cm / metal stem / amber glass / grey-transparent cable 150 cm

MR130GR / H 130 cm / metal stem / green glass / grey-transparent cable 150 cm

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
-	extra-low-voltage 12V DC LED bulb	G4 bulb (IP65 lampholder)*	1x1,5W	150	2700	85	A+	not included available on request	-




Sypha (outdoor)

[Finishes] // **Stems** - the stems of the Sypha collection are made of brass (Syphaduepassi) or black coloured iron (Syphasera and Syphasfera). On request we can supply solutions suitable for immersion into water.

[Note] // (*) IP specifics: lampholder IP65 (not protected against immersion); wires and connectors IP68; drivers IP67; IP average rate of the lamp 44.

p. 253




Syphasera / standing lamp / driver and accessories not incl. (see pages 106-111)

SYS65 / H 65 cm / black stem / brass details / opaline glass / grey-transparent cable 255 cm
 SYS80 / H 80 cm / black stem / brass details / opaline glass / grey-transparent cable 240 cm
 SYS110 / H 110 cm / black stem / brass details / opaline glass / grey-transparent cable 210 cm
 SYS140 / H 140 cm / black stem / brass details / opaline glass / grey-transparent cable 180 cm

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
-	extra-low-voltage 12V DC LED bulb	G4 bulb (IP65 lampholder)*	1x1,5W	150	2700	85	A+	not included available on request	-

p. 256




Syphasfera / standing lamp / driver and accessories not incl. (see pages 106-111)

SYF60 / H 60 cm / black stem / brass details / transparent glass / grey-transparent cable 255 cm
 SYF60I / H 60 cm / black stem / brass details / irreg. transp. glass / grey-transparent cable 255 cm
 SYF75 / H 75 cm / black stem / brass details / transparent glass / grey-transparent cable 240 cm
 SYF75I / H 75 cm / black stem / brass details / irreg. transp. glass / grey-transparent cable 240 cm
 SYF105 / H 105 cm / black stem / brass details / transparent glass / grey-transparent cable 210 cm
 SYF105I / H 105 cm / black stem / brass details / irreg. transp. glass / grey-transparent cable 210 cm
 SYF135 / H 135 cm / black stem / brass details / transparent glass / grey-transparent cable 180 cm
 SYF135I / H 135 cm / black stem / brass details / irreg. transp. glass / grey-transparent cable 180 cm

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
-	extra-low-voltage 12V DC LED bulb	G4 bulb (IP65 lampholder)*	1x1,5W	150	2700	85	A+	not included available on request	-

p. 259



Syphaduepassi / standing lamp / driver and accessories not incl. (see pages 106-111)

SYD45 / H 45 cm / brass stem and details / grey-transparent cable 225 cm
 SYD75 / H 75 cm / brass stem and details / grey-transparent cable 195 cm

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimming
-	extra-low-voltage 12V DC LED bulb	G4 bulb (IP65 lampholder)*	1x1,5W	150	2700	85	A+	not included available on request	-




Fil de Fer (outdoor)

[*Finishes*] // **Rough iron** (untreated metal) is chosen by the designer specifically because of its uniqueness and its natural ageing property. The appearance of any uneven rust patches does not constitute a defect, since it is a typical sign of the ageing process, which might be considerably accelerated in conditions of high humidity or direct exposure to outdoor weathering.

[*Cables*] // (**s**) suspension cable. / (**el**) electrical cable.

[*Note*] // (*) The drivers for the dimmable version of our outdoor products are larger than their not-dimmable standards. They are available on request with custom sized bases and boxes (see our website for further references). / (**) IP specifics: lampholder IP65 (not protected against immersion); wires and connectors IP68; drivers IP67; IP average rate of the lamp 44.

p. 263




Fil de Fer / outdoor pendant lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
F5SIPL / Ø 50 cm / aluminium / steel cables ^(s) / metal braided cable ^(el) / chrome base	110V or 240V	extra-low-voltage 12V DC LED bulb	G4 bulbs (IP65 lampholder)**	8x1,5W 12W	1200	2700	85	A+	electronic 12V DC IP67	NO* (available on request)
F7SIPL / Ø 70 cm / aluminium / steel cables ^(s) / metal braided cable ^(el) / chrome base				16x1,5W 24W	2400					
F10SIPL / Ø 100 cm / aluminium / steel cables ^(s) / metal braided cable ^(el) / chrome base				20x1,5W 30W	3000					

weight: Ø 50 8,5 kg / Ø 70 13 kg / Ø 100 18 kg

p. 264




Fil de Fer F / outdoor floor lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
F5IPL / Ø 50 cm / aluminium / metal braided cable / black box and plug cable	220-240V (110V available on request)	extra-low-voltage 12V DC LED bulb	G4 bulbs (IP65 lampholder)**	8x1,5W 12W	1200	2700	85	A+	electronic 12V DC IP67	NO* (av. on request)
F7IPL / Ø 70 cm / aluminium / metal braided cable / black box and plug cable				16x1,5W 24W	2400					
F10IPL / Ø 100 cm / aluminium / metal braided cable / black box and plug cable				20x1,5W 30W	3000					

cable 12V 450 cm / cable 230V (EU or CH) 200 cm

p. 269



Uomo della Luce XXL / outdoor standing lamp

	voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
UIPL / rough iron structure / aluminium sphere / black cable, box and plug cable	220-240V (110V av. on request)	extra-low-voltage 12V DC LED bulb	G4 bulbs (IP65 lampholder)**	20x1,5W 30W	3000	2700	85	A+	electronic 12V DC IP67	NO* (av. on request)

cable 12V 350 cm / cable 230V (EU or CH) 200 cm



Other Smiths

[*Finishes*] // **Brass** (an alloy of copper and zinc) is a very elegant finish, yellow-gold in colour, with an excellent corrosion resistance. We use it untreated, therefore it may oxidise with time. Regular cleaning helps preserving its original appearance and slow down the ageing process, which might be anyway accelerated by the weather, frequent handling or conditions of high humidity.

p. 275

Ø 26 cm ca



54 cm ca.

Alchemie T / table lamp

AHT / brass disc / alabaster diffuser / Medea limestone base

voltage	source	type	watt	lumen	K	CRI	en. class	driver/transformer	dimmer
110-240V	constant voltage 24V LED	low voltage LED strip	12W	1300	3000	>95	A++	constant voltage plug driver	NO on/off switch incl.

TECHNICAL INFORMATION



MAINS VOLTAGE LED

The LED modules and COB LED we supply in the Lederam and Medousé collection can be connected directly to the mains voltage because they do not require any driver (other than the one already mounted on the module). Compared to traditional light sources, mains voltage LED modules are more sensitive to any interference in the electricity mains, including voltage fluctuation and harmonic distortion, because they have a faster response to changes in voltage. This means that consequently to this variations occasional flickering or functioning anomaly may occur, but since not depending on the product, they cannot be considered a flaw or defect. Further than by problems on the line voltage, fluctuations and harmonics may be produced by variable power loads, as those caused by many types of motors and electronic devices. In case of anomalies we suggest to check the electrical system to apply protective modules reducing overvoltage at the connection terminals of electronic components. By means of this modules / filters, any residual voltage is then reduced to an appropriate protective level in relation to the discharge current.


Dimming

Mains voltage LED modules and COB LED are dimmable using IGBT (trailing edge) dimmers designed specifically for LED sources. Their dimming is extremely delicate: incompatible dimmers may cause irreparable damage to the LED. Some dimmers on the market have a NO button (Normally Open button) or they are specific connector socket-mounted or recessed. They are generally inserted into junction boxes; their limited thickness facilitates the installer's task and makes the dimmer fit for installation even in shallow boxes. Dimmers with an integrated radio dimmer for both manual (NO button) and wireless control are also available. It is important to note that during adjustment (for instance with a cord dimmer) the dimming appears less precise, with some flickering. Furthermore some types of dimmer, even if they have been recommended by the manufacturers themselves, have visible flickering (almost essentially down to a minimum) depending on the mains and on the type of interference present. The problem can be solved by increasing the minimum value setting of the potentiometer on the dimmer.


LED module

LED module
(Medousé)


COB LED



17W
28W




17W
29W




15W
30W




NO (Normally Open) Button



Socket-mounted or recessed




Wireless





LEDERAM: COLOUR COMBINATIONS AND DETAILS


Lederam Manta S1/S2/CWS1 / C150 / C180



code	shade		rods	discs	base
	external	internal			
3	black	gold	black	gold	black
4	black	copper	black	copper	black
5	white	white	gold	white	white
6	white	gold	satin	white	white
8	white	white	satin	white	white
10*	white	white	white	white	white


* Finish not available for model Lederam Manta S2

Lederam C1 / C2 / C3 / WB1 / W2



code	discs	rods	base
2	black	satin	black
3	gold	black	black
4	copper	black	black
5	white	gold	white
6	white	satin	white


Lederam W



code	disc 1		disc 2		base
	external	internal	internal	external	
1	black	copper	copper	black	black
2	black	gold	gold	black	black
3	gold	gold	gold	white	white
4	copper	copper	copper	white	white
5	white	gold	gold	white	white
6	white	copper	copper	white	white




Lederam W1




code	disc		joint	base
	external	internal		
1	black	black	nickel	black
3	gold	black	nickel	black
4	copper	black	nickel	black
6	white	white	nickel	white

Lederam WF



code	disc		base
	external	external	
1	black	black	black
3	gold	white	white
4	copper	white	white
6	white	white	white

Lederam F0 / F1 / F2 / F3 / T1







code	discs	rods	base	cable	dimmer
2	black	satin	black	black	black
3	gold	black	black	black	black
4	copper	black	black	black	black
5	white	gold	white	white	white
6	white	satin	white	white	white
12*	brass	black	black	black	black

* Finish available for model Lederam F0 only



CHANDELIER

GOLD MOON	JACKIE O	POSTKRISI	SWEET LIGHT
<p>Gold Moon Chandelier is supplied with single pendants with black wires, irregular black/gold shade dia. 20 cm ca. and copper curl directing the beam of light upwards to the shade. Each shade is handmade, therefore the dimensions can slightly change from pendant to pendant.</p> <p>NB the minimum amount of Gold Moon per Chandelier is 20 pendants.</p> 	<p>Jackie O Chandelier is supplied with single pendant with blue cable and nickel curl with lens, to define the beam of light of each pendant.</p> 	<p>PostKrisi Chandelier is supplied with natural fibreglass spheres with a diameter of 14 or 20 cm. On request it is also available with spheres in different colours or lined with gold/silver/copper coloured leaf.</p> 	<p>Sweet Light Chandelier is supplied with aluminium spheres with a diameter of 10 cm. On request it is also available with brass or silver coloured spheres.</p> 

Bases

The Chandeliers are supplied with satin steel bases in different dimensions.



square

30x30x5 cm / 60x60x5 cm / 90x90x5 cm



rectangular

150x30x5 cm / 150x60x5 cm / 90x30x5 cm




round

Ø 40 cm / Ø 78 cm

The bases of the Chandeliers are modular and very easy to install.

The satin finish steel plates are anchored to the white painted metal frame by means of suspension chains that facilitate both installation and maintenance. They are then secured in place with square head screws; the nickel cube that covers the screw remains exposed (see drawing). The steel plate is available on request white painted.




GOLD MOON	JACKIE O	POSTKRISI	SWEET LIGHT
-----------	----------	-----------	-------------

Standard Jack Mounting (NOT ADJUSTABLE HEIGHT)

Each pendant is mounted onto the base by means of a connection jack that fits in and locks in place in a simple motion. The base can therefore be shipped separately from the pendants, facilitating both the shipping and installation itself.

STANDARD

The standard maximum height of the codified Jackie O Chandeliers is 120 cm (obtained from H of base 5 cm + max pendant height of 115 cm). Starting from the maximum height, the cable lengths descend 7 times by about 5 cm.




ON REQUEST

By choosing the maximum cable length (up to max 300 cm – dimensions rounded up to the nearest 5 cm) and downsizing while retaining the proportions of the standard codes, a custom made composition can be produced. Any further customisation entails a bespoke design requiring a quotation (customized production).

NB Each capillary is manually bent. A tolerance of about 1 to 2 cm on the given cables lengths must be considered as acceptable

STANDARD

The standard maximum heights of the codified PostKrisi and Sweet Light Chandeliers are 180/300/400 cm (obtained from H of base 5 cm + max pendant height of 175/295/395 cm).




ON REQUEST

By choosing the maximum cable length (up to max 300 cm – dimensions rounded up to the nearest 5 cm) and downsizing while retaining the proportions of the standard codes, a custom made composition can be produced. Any further customisation entails a bespoke design requiring a quotation (customized production).

On Request (ADJUSTABLE HEIGHT)


TENSIONER

The version with a tensioner is available in those cases where the length of the cable requires adjustment during installation. The tensioner is supplied disassembled. Once you have placed the cable at the desired height, it must be cut and reconnected to the inside of the base (this operation helps preventing voltage drops and tangled cables inside the base).



CABLE LOCKING

The version with cable locking is available in those cases where the length of the cable requires adjustment during installation or in case of custom chandelier with bigger PostKrisi spheres (dia. 40 or 60 cm). The cable locking is supplied disassembled. Once you have placed the cable at the desired height, it must be cut and reconnected to the inside of the base (this operation helps preventing voltage drops and tangled cables inside the base).




Custom

On request we can supply customized designs with different base dimensions, a different number of pendants or with a tensioner instead of a jack connection. The PostKrisi and Sweet Light pendants are interchangeable on the bases, therefore we can also supply mixed Chandeliers.



MACCHINA DELLA LUCE LED BOARDS




Mod. A		Mod. E	
18W β	Ø 80 cm	12W α	Ø 50 cm
12W α	Ø 30 cm	12W α	Ø 30 cm
12W α	Ø 18 cm	12W α	Ø 18 cm
42W	4410 lumen	24W	2520 lumen
Mod. B		Mod. F**	
12W α	Ø 80 cm	24W γ	Ø 120 cm
12W α	Ø 18 cm	18W β	Ø 80 cm
12W	1260 lumen	18W β	Ø 50 cm
Mod. C		Mod. I	
24W γ	Ø 120 cm	18W β	Ø 80 cm
18W β	Ø 80 cm	12W α	Ø 50 cm
18W β	Ø 50 cm	12W α	Ø 30 cm
42W	4410 lumen	30W	3150 lumen
Mod. D*			
18W β	Ø 120 cm		
18W β	Ø 80 cm		
18W β	Ø 50 cm		
12W α	Ø 30 cm		
12W α	Ø 18 cm		
60W	6300 lumen		

* 110V version available with 4x α 12W / tot. 48W max
 ** 110V version available with 2x β 18W / 1x α 12W / tot. 48W max









STCHU-MOON LED BOARDS









1x 5W / 500 lumen		Stchu-Moon 05	
		Stchu-Moon 01	Ø 40 cm
		Stchu-Moon 01	Ø 60 cm
2x 5W / 1000 lumen		Stchu-Moon 09	
		Stchu-Moon 02	Ø 40/60 cm
4x 5W / 2000 lumen		Stchu-Moon 02	Ø 80/100 cm
6x 5W / 3000 lumen	3x	Stchu-Moon 02 Chandelier	

**OUTDOOR: GEL BOX SYSTEM**

	MB1 Mini gel box IP68
	5,3x3,9x2,4 cm
	(max 2 connections - connectors included)
	MB2 Mini gel box IP68
	5,2x5,3x2,9 cm
	(max 6 connections - connectors included)
	KP1 Extension cord kit
	5 mt
	with mini gel box IP68 for single connection
	(max 1 lamp)
	ED6 Driver 10W 12V DC 220-240V IP67
	7x3,7x2,3 cm / cables 45 cm ca.
	not dimmable
	(max 6 lamps)
	ED7 Driver 30W 12V DC 220-240V IP67
	11x3,7x2,3 cm / cable 12V 45 cm ca. / plug cable 200 cm
	not dimmable
	(max 20 lamps)
	ED7D Driver 30W 12V DC 220-240V IP67
	8x8x3 cm / cables 12V 45 cm ca. / plug cable 200 cm
	Triac dimmable
	(max 20 lamps)

**OUTDOOR: QUICK CONNECTORS SYSTEM**

	ED6CR Driver 10W 12V DC 220-240V IP67
	230V and 12V connectors included
	3,7x2,3x7 cm - cables 45 cm ca.
	not dimmable
	CRM Quick IP68 multiple connector / 1 IN & 5 OUT 12V
	(max 5 connections)
	CRS Quick IP68 IN single connector
	KP2 Extension cord kit with quick IP68 connectors CRS
	5 mt
	(max 1 lamp)
	FKIPL Kit box driver
	Ø 5x20 cm / cable 12V 45 cm / plug cable 200 cm
	not dimmable (driver ED7)
	standard
	FKIPLD Kit box driver
	16x10x4 cm / cable 12V 45 cm / plug cable 200 cm
	Triac dimmable (driver ED7D)
	available on request



OUTDOOR ACCESSORIES

	MSMP	Supporting modular plate
		for More (MR70/MR100/MR130)
		32x32x32 cm
		(max 4 lamps)
	MPT	Peg
		for More (MR70/MR100/MR130)
		25 cm
	MSM	Supporting plate
		for Medousé F
		31x31 cm ca.
	MDCV	Plug cable 230V standard EU (CH available on request)
		for Medousé F
		350 cm




MEDOUSÉ INSTALLATION SUGGESTIONS

WARNING

For stability reasons the lamp must be fastened to a solid surface such as a well or basement; in alternative it can be mounted on the modular supporting plate (ref. L / code MSM) available on request. Before installing the lamp, please check the levelling of the soil and make sure that it can support the weight of the fitting.



(Medousé weight Ø 30 cm 15 kg / Ø 50 cm 31 kg)



lamp base with holes for the fastening
(plugs not included)



Example 1

with basement and supply cable from the side





Example 2

with well and supply cable from underneath



Example 3


with supporting plate 1x code MSM
with plug cable 230V 1x code MDCV






Installation suggestions for Outdoor / GEL BOX system


1	Connection type	For models	Power supply	Access. applied
	GEL BOX system (without well)	Syphasera/Syphasfera/Syphaduepassi/More	code ED6	1x code ED6 1x code MB1 1x code MB2



2	Connection type	For models	Power supply	Access. applied
	GEL BOX system (with well)	Syphasera/Syphasfera/Syphaduepassi/More	provided by client	1x code MB2 1x code KP1




3	Connection type	For models	Power supply	Access. applied
	GEL BOX system (without well)	More (MR70/MR100/MR130)	code ED6	1x code ED6 1x code MB1 1x code MB2 1x code MSMP 3x code MPT*




Installation suggestions for Outdoor / GEL BOX system and QUICK CONNECTORS system


4	Connection type	For models	Power supply	Access. applied
	GEL BOX system (with well)	More (MR70/MR100/MR130)	provided by client	1x code MB2 1x code MSPT 3x code MPT



5	Connection type	For models	Power supply	Access. applied
	QUICK CONNECTORS system	Syphasera/Syphasfera/Syphaduepassi/More	code ED6CR	1x code ED6CR 1x code CRM 5x code CRS 1x code KP2




6	Connection type	For models	Power supply	Access. applied
	QUICK CONNECTORS system	Syphasera/Syphasfera/Syphaduepassi/More	code ED7CR	1x code ED7CR* 2x code CRM 9x code CRS *without plug cable, with mains voltage connectors





PSU (POWER SUPPLY UNIT) KITS



By means of the PSU kit, multiple LED lamps can be controlled simultaneously through an in-series board connected to a driver.

In the event of a failure of even a single LED, the board allows the other lamps to continue working properly.

It is advisable to install the kit in a technical compartment accessible for inspection at a maximum distance of about 5 meters from the point of installation of the jacks or tensioners, in order to avoid voltage drops.

The technical compartment must be located in an easily accessible place and large enough to accommodate both the wired in-series board and the power supply.

DRIVERS			PSU KITS	
ED0	rated voltage	220-240V / 50-60 Hz	K0WS	6W driver kit
	rated output	6W 350 mA / max 6x1W LED		not dimmable
	dimnable	NO		max 5x1W lamps
	dimensions	6 x 3,5 x 2 cm		
ED1	rated voltage	220-240V / 50-60 Hz	K1WS	6W driver kit
	rated output	6W 350 mA / max 6x1W LED		1...10V-PUSH dimmable
	dimnable	YES / 1...10V or push		max 5x1W lamps
	dimensions	6 x 5 x 2 cm		
ED4	rated voltage	110-240V / 50-60 Hz	K6WS	39W driver kit
	rated output	39W 350 mA 220/240V		1...10V-PUSH-DALI dimmable
	dimnable	YES / 1...10V, push or DALI		max 21x1W lamps
	dimensions	12,5 x 8 x 2,5 cm		
ALI0087	rated voltage	220-240V / 50-60 Hz	K7WS	24,5W driver kit
	rated output	24,5W 350 mA 220/240V		Triac/IGBT dimmable
	dimnable	YES / Triac/IGBT		max 20x1W lamps
	dimensions	16,5 x 4,5 x 4 cm		



DIMMING WIRING DIAGRAMS

Diagram 1 - IGBT - TRIAC

— 1 wire for power supply
— 1 wire for dimming




Diagram 2 - PUSH

— 2 wires for power supply
— 2 wires for dimming

WARNING: you need two extra wires, marked in red, in order to dim.





Diagram 3 - 1...10V - DALI

— 2 wires for power supply
— 2 wires for dimming

WARNING: you need two extra wires, marked in red, in order to dim.



Catellani & Smith Srl

Offices
via Cimitero 1/A
I-24020 Villa di Serio BG
T. +39 035 656088
info@catellanismith.com

Show-room
T. +39 035 210193
show-room@catellanismith.com

www.catellanismith.com



Catellani & Smith®

